


CRUISE REPORT: RF17-07

Created: January 2025, Updated: July 2025



Highlights

Cruise Summary Information

Section Designation	P13N
Expedition Designation (ExpoCode)	49UP20170623
Chief Scientist	Naoki NAGAI, JMA
Dates	Leg 1: 23 June – 13 July 2017 Leg 2: 17 July – 7 August 2017
Ship	R/V Ryofu Maru
Ports of Call	Leg 1: Tokyo – Hakodate Leg 2: Hakodate - Tokyo
Geographic Boundaries	145° 6"E 50° 02"N 165° 05"E 28° 98"N
Stations	46
Floats and Drifters Deployed	0
Moorings Deployed and Recovered	0

Contact Information:

Toshiya NAKANO

Global Environment and Marine Department, Japan Meteorological Agency (JMA)

1-3-4, Otemachi, Chiyoda-ku, Tokyo 100-8122, Japan

Phone: +81-3-3212-8341, Ext. 5131

Email: seadata@met.kishou.go.jp

Report assembled by Savannah Lewis

Contents

A. [Cruise narrative](#)

B. Underway measurements

1. *Navigation (to be submitted in the next update)*
2. *Bathymetry (to be submitted in the next update)*
3. [Maritime Meteorological Observations](#)
4. [Thermosalinograph](#)
5. [Underway Chlorophyll-a](#)

C. [Hydrographic Measurement Techniques and Calibration](#)

1. [CTD/O₂ Measurements](#)
2. [Bottle Salinity](#)
3. [Bottle Oxygen](#)
4. [Nutrients](#)
5. [Phytopigment \(Chlorophyll-a and phaeopigments\)](#)
6. [Total Dissolved Inorganic Carbon \(DIC\)](#)
7. [Total Alkalinity \(TA\)](#)
8. [pH](#)

A. Cruise narrative

1. Highlights

Cruise designation: RF17-07 (WHP-P13N revisit)

1. EXPOCODE: 49UP20170623

2. Chief scientist: Naoki NAGAI

Marine Division

Global Environment and Marine Department

Japan Meteorological Agency (JMA)

3. Ship name: R/V Ryofu Maru

4. Ports of call: Leg 1: Tokyo – Hakodate, Leg 2: Hakodate – Tokyo

5. Cruise dates (JST): Leg 1: 23 June 2017 – 13 July 2017

Leg 2: 17 July 2017 – 7 August 2017

6. Principal Investigator (Contact person):

Toshiya NAKANO

Marine Division

Global Environment and Marine Department

Japan Meteorological Agency (JMA)

1-3-4, Otemachi, Chiyoda-ku, Tokyo 100-8122, JAPAN

Phone: +81-3-3212-8341 Ext. 5131

E-mail: seadata@met.kishou.go.jp

2. Cruise Summary Information

RF17-07 cruise was carried out during the period from June 23 to August 7, 2017. The cruise started from the south of Hokkaido, Japan, and sailed southeastern line along the Kuril Islands, thereafter from 50°N to 29°N along approximately 165°E meridian. This line (WHP-P13) was observed by JMA in 2011 as CLIVER (Climate Variability and Predictability Project) / GO-SHIP (Global Ocean Ship-based Hydrographic Investigations Program).

A total of 46 stations was occupied using a Sea-Bird Electronics (SBE) 36 position carousel equipped with 10-liter Niskin water sample bottles, a CTD system (SBE911plus) equipped with SBE35 deep ocean standards thermometer, JFE Advantech oxygen sensor (RINKO III), Teledyne Benthos altimeter (PSA-916D), and Teledyne RD Instruments L-ADCP (300kHz). To examine consistency of data, we carried out the observation twice at 42°N, 165°E (Stn.26 and 27). Cruise track and station location are shown in Figure A.1.

At each station, full-depth CTDO₂ (temperature, conductivity (salinity) and dissolved oxygen) profile were taken, and up to 36 water samples were taken and analyzed. Water samples were obtained from 10 dbar to approximately 10 m above the bottom. In addition, surface water was sampled by a stainless steel bucket at each station. Sampling layer is designed as so-called staggered mesh as shown in Table A.1 (*Swift*, 2010). The bottle depth diagram is shown in Figure A.2.

Water samples were analyzed for salinity, dissolved oxygen, nutrients, dissolved inorganic carbon (DIC), total alkalinity (TA), pH, CFC-11, CFC-12, CFC-113 and phytopigment (chlorophyll-*a* and phaeopigments). Underway measurements of partial pressure of carbon dioxide (*p*CO₂), temperature, salinity, chlorophyll-*a*, subsurface current, bathymetry and meteorological parameters were conducted along the cruise track.

R/V Ryofu Maru departed Tokyo (Japan) on June 23, 2017. The hydrographic cast of CTDO₂

was started at the first station (Stn.1 (42°50'N, 145°37'E; RF6029)) on June 25. Leg 1 consisted of 26 stations from Stn.1 to Stn.26 (42°N, 165°E; RF6054). The observation at Stn.26 was finished on July 7. She called for Hakodate (Japan) on July 13 (Leg 1). She left Hakodate on July 17, 2017. The hydrographic cast of CTDO₂ was restarted at the station (Stn.27 (42°N, 165°E; RF6055)) on July 20. Leg 2 consisted of 20 stations from Stn.27 to Stn.46 (29°N, 165°E; RF6074). Stn.46 was finished on July 29. She arrived at Tokyo (Japan) on August 7, 2017 (Leg 2).




Figure A.1. The track and the station location of the cruise.




Figure A.2. The bottle depth diagram for the cruise.

Table A.1. The scheme of sampling layer in meters.

<i>Bottle count</i>	<i>scheme1</i>	<i>scheme2</i>	<i>scheme3</i>	<i>Bottle count</i>	<i>scheme1</i>	<i>scheme2</i>	<i>scheme3</i>
1	10	10	10	21	1800	1870	1730
2	25	25	25	22	2000	2070	1930
3	50	50	50	23	2200	2270	2130
4	75	75	75	24	2400	2470	2330
5	100	100	100	25	2600	2670	2530
6	125	125	125	26	2800	2870	2730
7	150	150	150	27	3000	3080	2930
8	200	200	200	28	3250	3330	3170
9	250	250	250	29	3500	3580	3420
10	300	330	280	30	3750	3830	3670
11	400	430	370	31	4000	4080	3920
12	500	530	470	32	4250	4330	4170
13	600	630	570	33	4500	4580	4420
14	700	730	670	34	4750	4830	4670
15	800	830	770	35	5000	5080	4920
16	900	930	870	36	5250	5330	5170
17	1000	1070	970	37	5500	5580	5420
18	1200	1270	1130	38	5750	5830	5670
19	1400	1470	1330	39	6000	6000	6000
20	1600	1670	1530				

At several deep stations over 36 layers, some layers were removed.

Table A.2. Station data of the cruise. The ‘RF’ column indicates the JMA station identification number.

<i>Leg</i>	<i>Station</i>		<i>Position</i>			<i>Leg</i>	<i>Station</i>		<i>Position</i>	
	<i>Stn.</i>	<i>RF</i>	<i>Latitude</i>	<i>Longitude</i>			<i>Stn.</i>	<i>RF</i>	<i>Latitude</i>	<i>Longitude</i>
1	1	6029	42-50.27 N	145-35.84 E		1	24	6052	44-00.46 N	165-03.43 E
1	2	6030	42-29.67 N	145-50.82 E		1	25	6053	43-00.59 N	165-01.20 E
1	3	6031	42-01.03 N	146-11.86 E		1	26	6054	42-00.82 N	165-01.40 E
1	4	6032	41-20.87 N	146-41.88 E		2	27	6055	42-00.91 N	165-00.50 E
1	5	6033	40-38.82 N	147-11.06 E		2	28	6056	41-00.78 N	165-00.14 E
1	6	6034	39-40.49 N	147-53.67 E		2	29	6057	40-00.41 N	164-59.19 E
1	7	6035	40-54.97 N	149-54.06 E		2	30	6058	38-59.26 N	165-00.67 E
1	8	6036	41-33.54 N	150-58.19 E		2	31	6059	38-00.20 N	165-01.09 E
1	9	6037	42-23.14 N	152-03.59 E		2	32	6060	37-29.89 N	164-59.14 E
1	10	6038	43-04.88 N	153-22.00 E		2	33	6061	37-00.86 N	164-59.42 E
1	11	6039	44-04.70 N	154-58.50 E		2	34	6062	36-29.56 N	164-59.71 E
1	12	6040	45-04.66 N	156-39.98 E		2	35	6063	35-58.33 N	165-01.95 E
1	13	6041	46-04.99 N	158-20.45 E		2	36	6064	35-30.41 N	165-00.45 E
1	14	6042	46-35.10 N	159-10.61 E		2	37	6065	35-00.36 N	164-59.14 E
1	15	6043	47-05.88 N	160-05.76 E		2	38	6066	34-29.01 N	164-58.84 E
1	16	6044	48-01.49 N	161-41.17 E		2	39	6067	33-59.02 N	165-00.04 E
1	17	6045	49-00.57 N	163-20.57 E		2	40	6068	33-29.29 N	164-58.59 E
1	18	6046	50-00.97 N	165-00.60 E		2	41	6069	32-58.78 N	165-00.17 E
1	19	6047	49-00.06 N	164-59.01 E		2	42	6070	32-29.44 N	165-00.78 E
1	20	6048	47-59.80 N	164-58.52 E		2	43	6071	31-59.10 N	165-02.18 E
1	21	6049	47-00.37 N	164-59.40 E		2	44	6072	31-00.73 N	164-57.35 E
1	22	6050	46-00.65 N	165-01.63 E		2	45	6073	30-00.81 N	164-59.59 E
1	23	6051	45-00.67 N	164-59.63 E		2	46	6074	28-58.96 N	164-59.84 E

3. List of Principal Investigators for Measurements

The principal investigators for each parameter are listed in Table A.3.

Table A.3. List of principal investigators for each parameter.

Hydrography	CTDO ₂ / LADCP	Keizo SHUTTA
	Salinity	Keizo SHUTTA
	Dissolve oxygen	Hiroyuki HATAKEYAMA
	Nutrients	Hiroyuki HATAKEYAMA
	Phytopigments	Hiroyuki HATAKEYAMA
	DIC	Shinji MASUDA
	TA	Shinji MASUDA
	pH	Shinji MASUDA
	CFCs	Yoshihiro SHINODA
	LADCP	Keizo SHUTTA
Underway	Meteorology	Naoki NAGAI
	Thermo-Salinograph	Shinji MASUDA
	<i>p</i> CO ₂	Shinji MASUDA
	Chlorophyll <i>a</i>	Hiroyuki HATAKEYAMA
	ADCP	Keizo SHUTTA
	Bathymetry	Keizo SHUTTA

Reference

Swift, J. H. (2010): Reference-quality water sample data: Notes on acquisition, record keeping, and evaluation. *IOCCP Report No.14, ICPO Pub. 134, 2010 ver.1*

3. Maritime Meteorological Observations

Dec 10, 2024

(1) Personnel

NAGAI Naoki (JMA)

(2) Data Period

08:00, 23 Jun. 2017 to 22:00, 10 Jul. 2017 (UTC).

08:00, 17 Jul. 2017 to 23:00, 01 Aug. 2017 (UTC).

(3) Methods

The maritime meteorological observation system on R/V Ryofu Maru is Ryofu Maru maritime meteorological measurement station (RMET). Instruments of RMET are listed in Table B.3.1. All RMET data were collected and processed by KOAC-7800 weather data processor made by KOSHIN DENKI KOGYO CO., LTD., Japan. The result of Maritime meteorological observation data were shown in Figures B.3.1 and B.3.2.

Table B.3.1. Instruments and locations of RMET.

Sensor	Parameter	Type (Manufacture)	Location (Height from maximum load line)
Thermometer	Air Temperature	R005-341 (CHINO CORPORATION)	Compass deck (13.3 m)
Hygrometer	Relative humidity	HMT3303JM (Vaisala)	Compass deck (13.3 m)
Thermometer	Sea surface temperature	RFN1-0 (CHINO CORPORATION)	Engine Room (-4.7 m)
Aerovane	Wind Speed Wind Direction	KVS-400-J (KOSHIN DENKI KOGYO CO., LTD.)	Mast top (19.8 m)
Wave gauge	Wave Height Wave period	Micro Wave WM-2 (Tsurumi-Seiki Co., Ltd.)	Ship front (6.5 m)
Barometer	Air pressure	PTB-220 (Vaisala)	Observation room (2.8 m)

Note that there are two sets of a thermometer and a hygrometer at the starboard and the port sides.




Figure B.3.1. Time series of (a) air temperature and sea surface temperature (SST), (b) relative humidity, (c) sea-level pressure, and (d) wind direction, wind speed and wave height. The light blue line in (d) panel shows the instrumental observation of wave height. Day 0 corresponds to June 23, 2017 (JST).




Figure B.3.2. Cruise tracks with wave height (a) from June 23 to July 11, 2017 (JST) and (b) from July 17 to August 2, 2017 (JST). Wind barbs are shown at all noon positions (JST) along the cruise track.

(4) Data processing and Data format

All raw data were recorded in every 6 seconds. The values of 1-minute and 10-minute data were averaged from 6-second raw data. The 10-minute data in every three hours are available from JMA web site (https://www.data.jma.go.jp/kaiyou/db/vessel_obs/data-report/html/ship/cruisedata_e.php?id=RF1707)

Because the thermometers and the hygrometers are equipped on the both starboard/port sides on the compass deck, we used air temperature/relative humidity data taken at upwind side at difference time. Dew point temperature was calculated from relative humidity and air temperature.

Pressure data were corrected to sea level pressure. During the cruise, fixed value +0.5 hPa (for the height of the observation room) was used for the correction. Data were stored in ASCII format and representative parameters are as follows; time in UTC, longitude (E), latitude (N), ship speed (knot), ship direction (degrees), sea-level pressure (hPa), air temperature (degrees Celsius), dew point temperature (degrees Celsius), relative humidity (%), sea surface temperature (degrees Celsius), wind direction (degrees) and wind speed (m/sec).

Wave height and period were observed twice in an hour. The measurement period was 20 minutes and each measurement started at 5 minutes and 35 minutes after the hour. In addition to those data, ship's position and observation time were recorded in ASCII format.

(5) Data quality

To confirm the data quality, each sensor was checked as follows.

Temperature/Relative humidity sensor:

The temperature and relative humidity (T/RH) sensors on the both sides of the ship were checked by the manufacturer before delivering and, they were also checked by the calibrated Assmann psychrometer before and after the cruise. The discrepancy between T/RH sensors and Assmann psychrometer were within ± 0.4 degrees Celsius and ± 4 %, respectively.

Thermometer (Sea surface temperature):

The sea temperature sensor was calibrated once a year by the manufacturer. Certificated accuracy of the sensor is better than ± 0.4 degrees Celsius. At the start of the cruise, the values are also compared with temperature of water, taken from sea surface using a bucket, which was measured by a calibrated mercury thermometer (Yoshino Keisoku S-441, accuracy is better than ± 0.1 degrees Celsius).

Pressure sensor:

Using calibrated portable barometer (Vaisala 765-16B, certificated accuracy is better than ± 0.1 hPa), pressure sensor was checked before the cruise. Mean difference of RMET pressure sensor and portable sensor is less than 0.7 hPa.

Aerovane:

Aerovane was checked once per year by the manufacturer, and once per five years by the Meteorological Instrument Center, JMA.

(6) Ship's weather observation

Non-instrumental observations such as weather, cloud, visibility, wave direction and wave height were made by the ship crews every three hours. We sent those data together with the RMET data to the Global Collecting Centre for Marine Climatological Data in IMMT (International Maritime Meteorological Tape) -V format. The RMET data are available from JMA web site.

(https://www.data.jma.go.jp/kaiyou/db/vessel_obs/data-report/html/ship/cruisedata_e.php?id=RF1707)

4. Thermo-Salinograph (TSG)

Nov 30, 2024

(1) Personnel

MASUDA Shinji (Leg 1)

SAKAMOTO Naoaki

SHINODA Yoshihiro

SUEMATSU Haruka

TANI Masanobu

TANIZAKI Chiho

(2) Instrument

(2.1) Overview

The Thermo-Salinograph (TSG) measurement system (EMS, Co., Ltd., Japan) consists of the SBE 38 (Digital oceanographic thermometer) and the SBE 45 (MicroTSG). The system was used for measuring temperature and salinity of surface seawater continuously along the cruise line.

The SBE 38 was used for measuring temperature of surface seawater and was placed near the seawater intake at the bottom of the vessel. The SBE 45 was used for calculating salinity, measuring temperature and conductivity of surface seawater in the laboratory of the vessel. The S/N and pre-cruise calibration date for these instruments were described in Table B.4.1. The pre-cruise calibration was performed at SBE, Inc., USA.

Table B.4.1 S/N and calibration date for the TSG system.

Instrument	S/N	Latest calibration date
SBE 38	3856783-0512	Sep 15, 2016
SBE 45	4556783-0301	Sep 17, 2016

(2.2) Temperature calculation

The temperature (T [°C]) for each instrument was calculated from the instrument output (p_i) and the coefficients (obtained at the pre-cruise calibration) with below formula:

$$T = 1 / \{ a_0 + a_1 [\ln(n)] + a_2 [\ln^2(n)] + a_3 [\ln^3(n)] \} - 273.15$$

$$p_i : \text{instrument output [counts]}$$

The coefficients for each instrument were described in Table B.4.2:

Table B.4.2 The coefficients for temperature calculation.

	SBE 38	SBE 45
a_c	6.945704e-05	2.493353e-05
a_1	2.679191e-04	2.741038e-04
a_2	-2.007703e-06	-2.428667e-06
a_3	1.393972e-07	1.500122e-07

(2.3) Conductivity calculation

The conductivity (\bar{C} [\bar{S}/\bar{m}]) was calculated from the instrument output (\bar{f}) of the SBE 45 and the coefficients (obtained at the pre-cruise calibration) with below formula:

$$\bar{C} = (g + h \times \bar{F}^2 + i \times \bar{F}^3 + j \times \bar{F}^4) / \{10 \times (1 + CT_{cor} \times t + CP_{cor} \times p)\}$$

$$\bar{F} = \bar{f} \times \sqrt{(1.0 + WBOTC \times t) / 100C}$$

\bar{f} : instrument output [Hz]

\bar{t} : temperature [$^{\circ}\text{C}$] obtained at SBE 45 measurement

\bar{p} : pressure [dbar] (=0)

$WBOTC$: 4.9027e-07

Other coefficients for calculating conductivity were described as Table B.4.3.

Table B.4.3 The coefficients for conductivity calculation.

	SBE 45
CT_{cor}	3.2500e-06
CP_{cor}	-9.5700e-08
g	-9.825666e-01
h	1.181159e-01
i	-2.822217e-04
j	3.470132e-05

(3) Measurement and calibration

Surface seawater was pumped up from the water intake at approximately 4 meters below the water level. First, the temperature of the seawater sample was measured by the SBE 38 and the data was collected every minute. Next, the seawater sample from the same line was de-bubbled and transferred to the laboratory, where the temperature and the conductivity were measured by the SBE 45 at a flow rate of approximately 1.2 L minute⁻¹. The data was collected at the same frequency.

For further on-board correction of the conductivity measurement by the SBE 45, the seawater samples were collected and stored from the same line in the 250 ml colorless bottle with a screw cap at least once a day. The salinity measurement of the collected samples was performed in the same method as the hydrographic salinity measurement, details of which are described in section ‘C-2 Bottle Salinity’. The coefficients (\bar{A} : slope, \bar{B} : offset) for the conductivity correction were determined using linear regression between the conductivity (calculated from the bottled samples salinity and the SBE45

temperature) and the SBE 45 conductivity, expressed as:

$$C_{corrected} = A \times C_{SBE45} + B$$

The determined coefficients are $A = 0.99929$ and $B = 0.002799$.

Finally, salinity was calculated from pressure, the corrected conductivity and the SBE45 temperature by PSS78 (Practical Salinity Scale, UNESCO).

(4) Data and Results

The data is distributed in “49UP20170623_P13N_TSG.CSV”. The record structure of JMA format is shown below.

Column1 DATE: Date (YYYYMMDD) [JST]

Column2 TIME: Time (HHMM) [JST] (= UTC + 9h)

Column3 LATITUDE: Latitude

Column4 LONGITUDE: Longitude

Column5 TEMP: Sea Surface Temperature (ITS-90) [$^{\circ}\text{C}$]

Column6 COND: Corrected Conductivity [S/m]

Column7 ONTEMP: Onboard Sea Temperature (ITS-90) [$^{\circ}\text{C}$]

Column8 SAL: Salinity (PSS78)

Reference

UNESCO (1981): Tenth report of the Joint Panel on Oceanographic Tables and Standards. *UNESCO Tech. Papers in Mar. Sci.*, 36, 25 pp.

5. Underway chlorophyll-*a*

10 October 2021

(1) Personnel

Hiroyuki HATAKEYAMA (GEMD/JMA)

Kei KONDO (GEMD/JMA)

(2) Method

The Continuous Sea Surface Water Monitoring System of fluorescence (Nippon Kaiyo, Japan) automatically had been continuously measured seawater which is pumped from a depth of about 4.5 m below the maximum load line to the laboratory. The flow rate of the surface seawater was controlled by several valves and adjusted to about 0.6 L min⁻¹. The sensor in this system is a fluorometer 10-AU (S/N: 7063, Turner Designs, United States).

(3) Observation log

The chlorophyll-*a* continuous measurements were conducted during the entire cruise; from 23 Jun. to 11 Jul., 2017 in Leg 1, and from 17 Jul. to 2 Aug., 2017 in Leg 2.

(4) Water sampling

Surface seawater was corrected from outlet of water line of the system at nominally 1 day intervals. The seawater sample was measured in the same procedure as hydrographic samples of chlorophyll-*a* (see Chapter C5 “Phytopigments”).

(5) Calibration

At the beginning and the end of legs, a raw fluorescence value of sensor was adjusted in sensitivity of the sensor using deionized water and a rhodamine 0.1ppm solution measured.

After the cruise, the fluorescence value was converted to chlorophyll-*a* concentration by programs in the system based on nearby water sampling data (chlorophyll-*a* concentration and distance from location of sensor data).

(6) Data

Underway fluorescence and chlorophyll-*a* data is distributed in JMA format in “49UP20170623_P13N_underway_chl.csv”. The record structure of the format is as follows;

Column1 DATE: Date (YYYYMMDD) [JST]

Column2 TIME: Time (HHMM) [JST] (= UTC + 9h)

Column3 LATITUDE: Latitude

Column4 LONGITUDE: Longitude

Column5 FLUOR: Fluorescence value (RFU)

Column6 CHLORA: Chlorophyll-*a* concentration (μg L⁻¹)

Column7 BTLCHL: Chlorophyll-*a* concentration of water sampling (μg L⁻¹).

C. Hydrographic Measurement Techniques and Calibration

1. CTDO₂ Measurements

8 June 2020

(1) Personnel

Keizo SHUTTA (GEMD/JMA)
 Yoshinobu ITO (GEMD/JMA)
 Noriyuki OKUNO (GEMD/JMA)
 Masahiro TANIGUCHI (GEMD/JMA)
 Kanako ISSHIKI (GEMD/JMA)

(2) CTDO₂ measurement system

(Software: SEASAVEwin32 ver7.23.2)

<i>Deck unit</i>	<i>Serial Number</i>	<i>Station</i>
SBE 11plus (SBE)	0683	RF6029 – 6074
<i>Under water unit</i>	<i>Serial Number</i>	<i>Station</i>
SBE 9plus (SBE)	69709 (Pressure: 1103)	RF6029 – 6074
<i>Temperature</i>	<i>Serial Number</i>	<i>Station</i>
SBE 3plus (SBE)	5632 (primary)	RF6029 – 6074
	4321 (secondary)	RF6029 – 6074
SBE 35 (SBE)	0062	RF6029 – 6074
<i>Conductivity</i>	<i>Serial Number</i>	<i>Station</i>
SBE 4C (SBE)	4316 (primary)	RF6029 – 6074
	3697 (secondary)	RF6029 – 6053
	4391 (secondary)	RF6054 – 6074
<i>Pump</i>	<i>Serial Number</i>	<i>Station</i>
SBE 5T (SBE)	7752 (primary)	RF6029 – 6046
	3854 (primary)	RF6047 – 6074
	6552 (secondary)	RF6029 – 6074
<i>Oxygen</i>	<i>Serial Number</i>	<i>Station</i>
RINKO III (JFE)	284 (foil number:141304A)	RF6029 – 6074
	026 (foil number:161209BA)	RF6029 – 6074
<i>Water sampler (36 position)</i>	<i>Serial Number</i>	<i>Station</i>
SBE 32 (SBE)	1144	RF6029 – 6074
<i>Altimeter</i>	<i>Serial Number</i>	<i>Station</i>
PSA-916D (TB)	43854	RF6029 – 6074
<i>Water Sampling Bottle</i>	<i>Station</i>	
Niskin Bottle (GO)	RF6029 – 6074	

SBE: Sea- Bird Electronics, Inc., USA

TB: Teledyne Benthos, Inc., USA

JFE: JFE Advantech Co., Ltd., Japan

GO: General Oceanics, Inc., USA

(3) Pre-cruise calibration

(3.1) Pressure

S/N 1103, 08 May 2017

c_1	=	$-4.282684e+004$	t_1	=	$3.006702e+001$
c_2	=	$5.097742e-001$	t_2	=	$-8.607997e-005$
c_3	=	$1.312000e-002$	t_3	=	$3.727820e-006$
d_1	=	$3.583800e-002$	t_4	=	$3.699030e-009$
d_2	=	$0.000000e+000$	t_5	=	$0.000000e+000$

Formula:

$$U(\text{degrees Celsius}) = M \times (12\text{-bit pressure temperature compensation word}) + B$$

U : temperature in degrees Celsius

S/N 1103 coefficients in SEASOFT (configuration sheet dated on 08 May 2017)

$$M = 1.28040e-002, B = -9.31868e+000$$

Finally, pressure is computed as

t : pressure period (μsec)

The drift-corrected pressure is computed as

$$\text{Slope} = 0.99998, \text{Offset} = -0.0312$$

(3.2) Temperature (ITS-90): SBE 3plus

S/N 5632(primary), 09 May 2017

$$\begin{aligned} g &= 4.34068491\text{e-}003 & j &= 1.37175196\text{e-}006 \\ h &= 6.27984816\text{e-}004 & f_0 &= 1000.0 \\ i &= 1.93705632\text{e-}005 \end{aligned}$$

S/N 4321(secondary), 05 May 2017

$$\begin{aligned} g &= 4.39120765\text{e-}003 & j &= 1.97534709\text{e-}006 \\ h &= 6.47474389\text{e-}004 & f_0 &= 1000.0 \\ i &= 2.31567780\text{e-}005 \end{aligned}$$

Formula:

f : Instrument freq.[Hz]

(3.3) Deep Ocean Standards Thermometer Temperature (ITS-90): SBE 35

S/N 0062, 25 Mar. 2006

$$\begin{aligned} a_0 &= 4.41977256\text{e-}003 & a_3 &= -1.01508095\text{e-}005 \\ a_1 &= -1.19652517\text{e-}003 & a_4 &= 2.17345047\text{e-}007 \\ a_2 &= 1.82077469\text{e-}004 \end{aligned}$$

Formula:

n : instrument output

The slow time drift of the SBE 35

S/N 0062, 09 Feb. 2017 (2nd step: fixed point calibration)

Slope = 1.000008, Offset = -0.001087

Formula:

(3.4) Conductivity: SBE 4C

S/N 4316(primary), 10 May 2017

$$\begin{array}{ll} g & = -9.86548223\text{e}+000 & j & = 2.20710052\text{e}-004 \\ h & = 1.28968399\text{e}+000 & CP_{cor} & = -9.5700\text{e}-008 \\ i & = -2.24867830\text{e}-003 & CT_{cor} & = 3.2500\text{e}-006 \end{array}$$

S/N 3697(secondary), 11 May 2017

$$\begin{array}{ll} g & = -1.01875765\text{e}+001 & j & = 1.38394615\text{e}-004 \\ h & = 1.58630748\text{e}+000 & CP_{cor} & = -9.5700\text{e}-008 \\ i & = -7.35121898\text{e}-004 & CT_{cor} & = 3.2500\text{e}-006 \end{array}$$

S/N 4391(secondary), 06 Oct. 2016

$$\begin{array}{ll} g & = -9.89505411\text{e}+000 & j & = 1.99921691\text{e}-004 \\ h & = 1.69446426\text{e}+000 & CP_{cor} & = -9.5700\text{e}-008 \\ i & = -1.20073826\text{e}-003 & CT_{cor} & = 3.2500\text{e}-006 \end{array}$$

Conductivity of a fluid in the cell is expressed as:

f : instrument frequency (kHz)

t : water temperature (degrees Celsius)

p : water pressure (dbar).

(3.5) Oxygen (RINKO III)

RINKO III (JFE Advantech Co., Ltd., Japan) is based on the ability of selected substance to act as dynamic fluorescence quenchers. RINKO III model is designed to use with a CTD system which accept an auxiliary analog sensor, and is designed to operate down to 7000 m.

RINKOIII output is expressed in voltage from 0 to 5 V.

(4) Data correction and Post-cruise calibration

(4.1) Temporal change of deck pressure and Post-cruise calibration

The drift-corrected pressure of post-cruise is computed as

$$P_{\text{corrected}} = P_{\text{measured}} - \text{Offset} + \text{Slope} \times \text{Days from 2017/6/23(days)}$$

S/N 1103, 14 Nov. 2017

Slope = 1.00001, Offset = -0.3662




Figure C.1.1. Time series of the CTD deck pressure. Red line indicates atmospheric pressure anomaly. Blue line and dots indicate pre-cast deck pressure and average.

(4.2) Temperature sensor (SBE 3plus)

The practical corrections for CTD temperature data can be made by using a SBE 35, correcting the SBE 3plus to agree with the SBE 35 (*McTaggart et al., 2010; Uchida et al., 2007*).

CTD temperature is corrected as

$$T_{\text{corrected}} = T_{\text{measured}} + c_0 + c_1 P + c_2 P^2$$

T : the CTD temperature (degrees Celsius), P : pressure (dbar) and c_0, c_1, c_2 : coefficients

Table C.1.1. Temperature correction summary (Pressure ≥ 2000 dbar). (Bold: accepted sensor)

<i>S/N</i>	<i>Num</i>	$c_0(K)$	$c_1(K/dbar)$	$C_2(K/dbar^2)$	<i>Stations</i>
5632	383	9.6179841e-4	-4.6702404e-7	7.9530814e-11	RF6029 – 6052 RF6053 – 6054
5632	330	1.3175747e-3	-6.9650780e-7	1.0301522e-10	RF6055 – 6074
4321	383	9.5947886e-4	1.4027547e-7	0.0000000e+0	RF6029 – 6052 RF6053 – 6054
4321	330	8.5661013e-4	1.4207755e-7	0.0000000e+0	RF6055 – 6074

Table C.1.2. Temperature correction summary for S/N 5632.

Stations	Pressure < 2000dbar			Pressure \geq 2000 dbar		
	Num	Average (K)	Std (K)	Num	Average (K)	Std (K)
RF6029 – 6054	532	–0.0003	0.0152	383	0.0000	0.0001
RF6055 – 6074	390	–0.0001	0.0068	330	0.0000	0.0002

Table C.1.3. Temperature correction summary for S/N 4321.

Stations	Pressure < 2000dbar			Pressure \geq 2000 dbar		
	Num	Average (K)	Std (K)	Num	Average (K)	Std (K)
RF6029 – 6054	532	0.0007	0.0141	383	0.0000	0.0002
RF6055 – 6074	390	0.0001	0.0071	330	0.0000	0.0002




Figure C.1.2. Difference between the CTD temperature (*S/N 4321*) and the Deep Ocean Standards thermometer (SBE 35) at Leg 1, accepted as reported data for RF6029 – 6052. Blue and red dots indicate before and after the correction using SBE 35 data respectively. Lower two panels show histogram of the difference after correction.




Figure C.1.3. Difference between the CTD temperature (*S/N* 5632) and the Deep Ocean Standards thermometer (SBE 35) at Leg 1, accepted as reported data for RF6053 – 6054. Blue and red dots indicate before and after the correction using SBE 35 data respectively. Lower two panels show histogram of the difference after correction.




Figure C.1.4. Difference between the CTD temperature (*S/N 4321*) and the Deep Ocean Standards thermometer (SBE 35) at Leg 2. Blue and red dots indicate before and after the correction using SBE 35 data respectively. Lower two panels show histogram of the difference after correction.

Post-cruise sensor calibration for the SBE 3plus

S/N 5632(primary), 31 Oct. 2017

$$\begin{aligned}
 g &= 4.34076529\text{e-}003 & j &= 1.39574219\text{e-}006 \\
 h &= 6.28151595\text{e-}004 & f_0 &= 1000.0 \\
 i &= 1.94809524\text{e-}005
 \end{aligned}$$

S/N 4321(secondary), 31 Oct. 2017

$$\begin{aligned} g &= 4.39124598\text{e-}003 & j &= 1.98482789\text{e-}006 \\ h &= 6.47553788\text{e-}004 & f_0 &= 1000.0 \\ i &= 2.32053922\text{e-}005 \end{aligned}$$

Formula:

f: Instrument freq.[Hz]

Post-cruise sensor calibration for the SBE 35

S/N 0062, 09 Feb. 2017 (2nd step: fixed point calibration)

Slope = 1.000008, Offset = -0.001087

Formula:

(4.3) Conductivity sensor (SBE 4C)

The practical corrections for CTD conductivity data can be made by using a bottle salinity data, correcting the SBE 4C to agree with measured conductivity (*McTaggart et al., 2010*).

CTD conductivity is corrected

C: CTD conductivity, *c_i* and *p_j*: calibration coefficients

i, j: determined by referring to AIC (*Akaike, 1974*). According to *McTaggart et al. (2010)*, maximum of *I* and *J* are 2.

Table C.1.4. Conductivity correction coefficient summary. (Bold: accepted sensor)

<i>S/N</i>	<i>Num</i>	<i>c₀</i> (S/m)	<i>c₁</i>	<i>c₂</i> (m/S)	<i>Stations</i>
			<i>p₁</i> (S/m/dbar)	<i>p₂</i> (S/m/dbar ²)	
4316	915	-3.1581e-3	1.8347e-3	-2.5633e-4	RF6029 – 6052
			7.5769e-8	-5.4876e-12	RF6053 – 6054
4316	738	2.3080e-3	-1.1553e-4	1.4675e-4	RF6055 - 6074
			8.7493e-8	-5.8058e-12	
3697	840	-2.0670e-4	0.0000e+0	0.0000e+0	RF6029 – 6052
			1.2017e-5	0.0000e+0	RF6053
4391	38	-1.7603e-4	0.0000e+0	0.0000e+0	RF6054
			5.7870e-7	-1.0264e-10	
4391	733	3.3513e-4	0.0000e+0	0.0000e+0	RFF6055 – 6074
			8.0921e-8	-8.1909e-12	

Table C.1.5. Conductivity correction and salinity correction summary for S/N 4316.

Stations	Pressure < 1900dbar					
	Conductivity			Salinity		
	Num	Average (S/m)	Std (S/m)	Num	Average	Std
RF6029 – 6054	472	0.0000	0.0001	472	0.0001	0.0018
RF6055 – 6074	368	0.0000	0.0002	368	0.0000	0.0015
Stations	Pressure ≥ 1900 dbar					
	Conductivity			Salinity		
	Num	Average (S/m)	Std (S/m)	Num	Average	Std
RF6029 – 6054	443	0.0000	0.0001	443	−0.0001	0.0007
RF6055 – 6074	370	0.0000	0.0001	370	0.0000	0.0007

Table C.1.6. Conductivity correction and salinity correction summary for S/N 3697.

Stations	Pressure < 1900dbar					
	Conductivity			Salinity		
	Num	Average (S/m)	Std (S/m)	Num	Average	Std
RF6029 – 6053	449	0.0000	0.0002	449	0.0000	0.0019
Stations	Pressure ≥ 1900 dbar					
	Conductivity			Salinity		
	Num	Average (S/m)	Std (S/m)	Num	Average	Std
RF6029 – 6053	391	0.0000	0.0000	391	0.0000	0.0006

Table C.1.7. Conductivity correction and salinity correction summary for S/N 4391.

Stations	Pressure < 1900dbar					
	Conductivity			Salinity		
	Num	Average (S/m)	Std (S/m)	Num	Average	Std
RF6054	23	0.0000	0.0012	23	0.0009	0.0119
RF6055 – 6074	364	0.0000	0.0001	364	0.0000	0.0015
Stations	Pressure ≥ 1900 dbar					
	Conductivity			Salinity		
	Num	Average (S/m)	Std (S/m)	Num	Average	Std
RF6054	15	0.0000	0.0001	15	−0.0008	0.0017
RF6055 – 6074	369	0.0000	0.0001	369	0.0000	0.0007




Figure C.1.5. Difference between the CTD conductivity (S/N 3697) and the bottle conductivity at Leg 1, accepted as reported data for RF6029 – 6052. Blue and red dots indicate before and after the calibration using bottle data respectively. Lower two panels show histogram of the difference before and after calibration.




Figure C.1.6. Difference between the CTD conductivity (S/N 4316) and the bottle conductivity at Leg 1, accepted as reported data for RF6053 – 6054. Blue and red dots indicate before and after the calibration using bottle data respectively. Lower two panels show histogram of the difference before and after calibration.




Figure C.1.7. Difference between the CTD conductivity (S/N 4391) and the bottle conductivity at Leg 2. Blue and red dots indicate before and after the calibration using bottle data respectively. Lower two panels show histogram of the difference before and after calibration.

Post-cruise sensor calibration for the SBE 4C

S/N 4316(primary), 31 Oct. 2017

g	$= -9.87098752\text{e}+000$	j	$= 2.45098543\text{e}-004$
h	$= 1.29122150\text{e}+000$	CP_{cor}	$= -9.5700\text{e}-008$
i	$= -2.61504107\text{e}-003$	CT_{cor}	$= 3.2500\text{e}-006$

S/N 3697(secondary), 22 Nov. 2017

$$\begin{array}{ll} g = -9.72709046\text{e}+000 & j = 3.58988626\text{e}-005 \\ h = 1.24366570\text{e}+000 & CP_{cor} = -9.5700\text{e}-008 \\ i = 2.09373055\text{e}-004 & CT_{cor} = 3.2500\text{e}-006 \end{array}$$

S/N 4391(secondary), 31 Oct. 2017

$$\begin{array}{ll} g = -9.89628688\text{e}+000 & j = 2.00907028\text{e}-004 \\ h = 1.69454692\text{e}+000 & CP_{cor} = -9.5700\text{e}-008 \\ i = -1.22312141\text{e}-003 & CT_{cor} = 3.2500\text{e}-006 \end{array}$$

Conductivity of a fluid in the cell is expressed as:

$$\sigma = \sigma_0 \left(1 + \frac{C_1}{f} + \frac{C_2}{f^2} + \frac{C_3}{f^3} + \frac{C_4}{f^4} + \frac{C_5}{f^5} + \frac{C_6}{f^6} + \frac{C_7}{f^7} + \frac{C_8}{f^8} + \frac{C_9}{f^9} + \frac{C_{10}}{f^{10}} \right) \left(1 + \frac{C_{11}}{t} + \frac{C_{12}}{t^2} + \frac{C_{13}}{t^3} + \frac{C_{14}}{t^4} + \frac{C_{15}}{t^5} + \frac{C_{16}}{t^6} + \frac{C_{17}}{t^7} + \frac{C_{18}}{t^8} + \frac{C_{19}}{t^9} + \frac{C_{20}}{t^{10}} \right) \left(1 + \frac{C_{21}}{p} + \frac{C_{22}}{p^2} + \frac{C_{23}}{p^3} + \frac{C_{24}}{p^4} + \frac{C_{25}}{p^5} + \frac{C_{26}}{p^6} + \frac{C_{27}}{p^7} + \frac{C_{28}}{p^8} + \frac{C_{29}}{p^9} + \frac{C_{30}}{p^{10}} \right)$$

f : instrument frequency (kHz)

t : water temperature (degrees Celsius)

p : water pressure (dbar).

(4.4) Oxygen sensor (RINKO III)

The CTD oxygen is calculated using RINKO III output (voltage) by the Stern-Volmer equation, according to a method by *Uchida et al. (2008)* and *Uchida et al. (2010)*. The pressure hysteresis for the RINKO III output (voltage) is corrected according to a method by *Sea-bird Electronics (2009)* and *Uchida et al. (2010)*. The formulas are as follows:

$$\begin{aligned} P_0 &= 1.0 + c_4 \times t \\ P_c &= c_5 + c_6 \times v + c_7 \times T + c_8 \times T \times v \\ K_{sv} &= c_1 + c_2 \times t + c_3 \times t^2 \\ coef &= (1.0 + c_9 \times P/1000)^{1/3} \\ [O_2] &= O_2^{\text{sat}} \times \{(P_0/P_c - 1.0)/K_{sv} \times coef\} \end{aligned}$$

P : pressure (dbar), t : potential temperature, v : RINKO output voltage (volt)

T : elapsed time of the sensor from the beginning of first station in calculation group in day

O_2^{sat} : dissolved oxygen saturation by *Garcia and Gordon (1992)* ($\mu\text{mol/kg}$)

$[O_2]$: dissolved oxygen concentration ($\mu\text{mol/kg}$)

c_1 – c_9 : determined by minimizing difference between CTD oxygen and bottle dissolved oxygen by quasi-newton method (*Shanno, 1970*).

Table C.1.8. Dissolved oxygen correction coefficient summary. (Bold: accepted sensor)

S/N	Stations	c_1	c_2	c_3	c_4	c_5
		c_6	c_7	c_8	c_9	
284	RF6029 – 6052	1.62761e+0	2.62014e–2	2.05448e–4	–1.43550e–5	–1.23262e–1
		2.97862e–1	–2.06456e–3	1.58910e–3	7.59679e–2	
284	RF6053 – 6054	1.62366e+0	2.71548e–2	1.85575e–4	2.16391e–4	–1.23241e–1
		2.98092e–1	–1.79515e–3	1.46727e–3	7.57775e–2	
284	RF6055 – 6074	1.64082e+0	3.16863e–2	2.07609e–4	1.30210e–3	–1.30341e–1
		3.03830e–1	9.25551e–5	7.25297e–4	7.94010e–2	
026	RF6029 – 6052	1.67324e+0	2.82278e–2	2.10147e–4	8.30189e–5	–1.39348e–1
		3.17475e–1	–1.96011e–3	1.10485e–3	8.24465e–2	
026	RF6053 – 6054	1.67018e+0	2.90568e–2	1.98152e–4	2.91550e–4	–1.39555e–1
		3.17743e–1	–1.63197e–3	9.71694e–4	8.23863e–2	
026	RF6055 – 6074	1.69880e+0	3.14867e–2	2.68243e–4	1.17187e–3	–1.44137e–1
		3.20740e–1	5.68790e–3	2.01386e–4	9.07287e–2	

Table C.1.9. Dissolved oxygen correction summary for S/N 284.

Stations	Pressure < 950dbar			Pressure ≥ 950 dbar		
	Num	Average (μmol/kg)	Std (μmol/kg)	Num	Average (μmol/kg)	Std (μmol/kg)
RF6029 – 6052	348	0.04	1.38	434	–0.02	0.32
RF6053 – 6054	363	0.03	1.37	458	–0.01	0.31
RF6055 – 6076	279	–0.02	1.10	402	0.00	0.48

Table C.1.10. Dissolved oxygen correction summary for S/N 026.

Stations	Pressure < 950dbar			Pressure ≥ 950 dbar		
	Num	Average (μmol/kg)	Std (μmol/kg)	Num	Average (μmol/kg)	Std (μmol/kg)
RF6029 – 6052	348	0.04	1.38	434	–0.02	0.32
RF6053 – 6054	608	–0.01	1.10	508	0.00	0.25
RF6055 – 6076	279	–0.02	1.12	402	–0.01	0.48




Figure C.1.8. Difference between the CTD oxygen (*S/N 284*) and bottle dissolved oxygen at Leg 1. Red dots in upper two panels indicate the result of calibration. Lower two panels show histogram of the difference between calibrated oxygen and bottle oxygen.

RINKO (S/N 284)




Figure C.1.9. Difference between the CTD oxygen (S/N 284) and bottle dissolved oxygen at Leg 2. Red dots in upper two panels indicate the result of calibration. Lower two panels show histogram of the difference between calibrated oxygen and bottle oxygen.

(4.5) Results of detection of sea floor by the altimeter (PSA-916D)

The altimeter detected the sea floor at 41 of 46 stations, the average distance of beginning detecting the sea floor was 46.8 m, and that of final detection of sea floor was 13.2 m. The summary of detection of PSA-916D was shown in Figure C.1.8.




Figure C.1.10. The summary of detection of PSA-916D. The left panel shows the stations of detection, the right panel shows the relationship among PSA-916D, bathymetry and CTD depth. In the left panel, closed and open circles indicate react and no-react stations, respectively.

References

- Akaike, H. (1974): A new look at the statistical model identification. *IEEE Transactions on Automatic Control*, **19**:716–722.
- García, H. E., and L. I. Gordon (1992): Oxygen solubility in seawater: Better fitting equations. *Limnol. Oceanogr.*, **37**, 1307–1312.
- McTaggart, K. E., G. C. Johnson, M. C. Johnson, F. M. Delahoyde, and J. H. Swift (2010): The GO-SHIP Repeat Hydrography Manual: A Collection of Expert Reports and guidelines. IOCCP Report No **14**, ICPO Publication Series No. 134, version 1, 2010.
- Sea-Bird Electronics (2009): SBE 43 dissolved oxygen (DO) sensor – hysteresis corrections, *Application note no. 64-3*, 7 pp.
- Shanno, David F. (1970): Conditioning of quasi-Newton methods for function minimization. *Math. Comput.* **24**, 647–656. MR 42 #8905.
- Uchida, H., G. C. Johnson, McTaggart, K. E. (2010): CTD oxygen sensor calibration procedures. In: The GO-SHIP repeat hydrography manual: A Collection of Expert Reports and guidelines. IOCCP Report No **14**, ICPO Publication Series No. 134, version 1, 2010.
- Uchida, H., K. Ohyama, S. Ozawa, and M. Fukasawa (2007): In-situ calibration of the Sea-Bird 9plus CTD thermometer. *J. Atmos. Oceanic Technol.*, **24**, 1961–1967.

Uchida, H., T. Kawano, I. Kaneko, and M. Fukasawa (2008): In-situ calibration of optode-based oxygen sensors. *J. Atmos. Oceanic Technol.*, **25**, 2271–2281.

2. Bottle Salinity

8 June 2020

(1) Personnel

Keizo SHUTTA (GEMD/JMA)

Yoshinobu ITO (GEMD/JMA)

Noriyuki OKUNO (GEMD/JMA)

Masahiro TANIGUCHI (GEMD/JMA)

Kanako ISSHIKI (GEMD/JMA)

(2) Salinity measurement

Salinometer: AUTOSAL 8400B (S/N68614; Guildline Instruments Ltd., Canada)

Thermometer: Guildline platinum thermometers model 9450 (to monitor an ambient temperature and bath temperature)

IAPSO Standard Sea Water: P160 ($K_{15}=0.99983$)

(3) Sampling and measurement

The measurement system was almost same as *Kawano* (2010).

Algorithm for practical salinity scale, 1978 (PSS-78; *UNESCO*, 1981) was employed to convert the conductivity ratios to salinities.

(4) Station occupied




Figure C.2.1. Location of observation stations of bottle salinity.




Figure C.2.2. Distance-depth distribution of sampling layers of bottle salinity.

(5) Result

(5.1) Ambient temperature, bath temperature and SSW measurements




Figure C.2.3. The upper panel, red line, black line and blue line indicate time-series of ambient temperature, ambient temperature average and bath temperature during cruise. The lower panel, black dots and red dots indicate raw and corrected time-series of the double conductivity ratio of the standard sea water (P160).

(5.2) Replicate and Duplicate Samples

We took replicate (pair of water samples taken from a single Niskin bottle) and duplicate (pair of water samples taken from different Niskin bottles closed at the same depth) samples of bottle salinity through the cruise. Results of the analyses are summarized in Table C.2.1. Detailed results of them are shown in Figure C.2.4. The calculation of the standard deviation from the difference of sets was based on a procedure (SOP 23) in *DOE* (1994).

Table C.2.1. Summary of replicate and duplicate analyses.

Measurement	Ave. \pm S.D.
Replicate	0.0003 \pm 0.0003 (N=156)
Duplicate	0.0007 \pm 0.0009 (N=5)




Figure C.2.4. Result of (left) replicate and (right) duplicate analyses during the cruise against (a) station number, (b) pressure and (c) salinity, and (d) histogram of the measurements. Green line indicates the mean of the differences of salinity of replicate/duplicate.

(5.3) Summary of assigned quality control flags

Table C.2.2. Summary of assigned quality control flags

Flag	Definition	Salinity
2	Good	1442
3	Questionable	55
4	Bad (Faulty)	10
6	Replicate measurements	173
Total number of samples		1680

References

- DOE (1994), Handbook of methods for the analysis of the various parameters of the carbon dioxide system in sea water; version 2. *A.G. Dickson and C. Goyet (eds), ORNL/CDIAC-74.*
- Kawano (2010), The GO-SHIP Repeat Hydrography Manual: A Collection of Expert Reports and Guidelines. *IOCCP Report No. 14, ICPO Publication Series No. 134, Version 1.*
- UNESCO (1981), Tenth report of the Joint Panel on Oceanographic Tables and Standards. *UNESCO Tech. Papers in Mar. Sci.*, **36**, 25 pp.

3. Bottle Oxygen

8 June 2020

(1) Personnel

Hiroyuki HATAKEYAMA (GEMD/JMA)

Daisuke SASANO (GEMD/JMA)

Kei KONDO (GEMD/JMA)

Satomi TANAKA (GEMD/JMA)

Rie SANAI (GEMD/JMA)

(2) Station occupied

A total of 46 stations (Leg 1: 26, Leg 2: 20) were occupied for dissolved oxygen measurements. Station location and sampling layers of bottle oxygen are shown in Figures C.3.1 and C.3.2, respectively.




Figure C.3.1. Location of observation stations of bottle oxygen. Closed and open circles indicate sampling and no-sampling stations, respectively.




Figure C.3.2. Distance-depth distribution of sampling layers of bottle oxygen.

(3) Instrument

Detector: DOT-15X (Kimoto Electronic, Japan)

Burette: APB-610 (Kyoto Electronic, Japan)

(4) Sampling and measurement

Methods of seawater sampling, measurement, and calculation of dissolved oxygen concentration were based on IOCCP Report (Langdon, 2010). Details of the methods are shown in Appendix A1.

The reagents for the measurement were prepared according to recipes described in Appendix A2. It is noted that standard KIO_3 solutions were prepared gravimetrically using the highest purity standard substance KIO_3 (Lot. No. TLG0272, Wako Pure Chemical, Japan). Batch list of prepared standard KIO_3 solutions is shown in Table C.3.1.

Table C.3.1. Batch list of the standard KIO_3 solutions.

KIO_3 batch	Concentration and uncertainty (k=2) at 20 °C. Unit is mol L⁻¹.	Purpose of use
20161018-1	0.0016668±0.0000003	Standardization (main use)
20161025-1	0.0016669±0.0000003	Mutual comparison

(5) Standardization

Concentration of $\text{Na}_2\text{S}_2\text{O}_3$ titrant was determined with the standard KIO_3 solution “20161018-1”, based on the methods of IOCCP Report (Langdon, 2010). The results of standardization during the cruise are shown in Figure C.3.3. Standard deviation of its concentration at 20 °C determined through standardization was used in calculation of an uncertainty.




Figure C.3.3. Calculated concentration of $\text{Na}_2\text{S}_2\text{O}_3$ solution at 20 °C in standardization during Leg 1 (top) and Leg 2 (bottom). Different colors of plots indicate different batches of $\text{Na}_2\text{S}_2\text{O}_3$ solution; red (blue) plots correspond to the left (right) y-axis. Error bars of plots show standard deviation of concentration of $\text{Na}_2\text{S}_2\text{O}_3$ in the measurement. Thick and dashed lines denote the mean and 2 times of standard deviations for the batch measurements, respectively.

(6) Blank

(6.1) Reagent blank

Blank in oxygen measurement (reagent blank; V_{blk}) can be represented as follows;

$$V_{\text{blk}} = V_{\text{blk-ep}} + V_{\text{blk-reg}} \quad (\text{C3.1})$$

where $V_{\text{blk-ep}}$ represents a blank due to differences between the measured end-point and the equivalence point, and $V_{\text{blk-reg}}$ a blank associated with oxidants or reductants in the reagent. The reagent blank V_{blk} was determined by the methods described in IOCCP Report (Langdon, 2010) using pure water. Because we used two sets (set A and B) of pickling reagent-I and -II, the blanks in each set were determined (Figure C.3.4).




Figure C.3.4. Reagent blank (V_{blk}) determination for set A (top) and set B (bottom). Error bars of plots show standard deviation of the measurement. Thick and dashed lines denote the mean and 2 times of standard deviations for the batch measurement, respectively.

(6.2) Other blanks

We also determined two other blanks related to oxygen measurement; blank $V_{\text{reg-blk}}$ and seawater blank ($V_{\text{sw-blk}}$). Details are described in Appendix A3.

(7) Quality Control

(7.1) Replicate and duplicate analyses

We took replicate (pair of water samples taken from a single Niskin bottle) and duplicate (pair of water samples taken from different Niskin bottles closed at the same depth) samples of dissolved oxygen through the cruise. Results of the analyses are summarized in Table C.3.2. Detailed results of them are shown in Figure C.3.5. The calculation of the standard deviation from the difference of sets was based on a procedure (SOP 23) in DOE (1994).

Table C.3.2. Summary of replicate and duplicate measurements.

Measurement	Ave. \pm S.D. ($\mu\text{mol kg}^{-1}$)
Replicate	0.21 ± 0.23 (N=175)
Duplicate	0.22 ± 0.23 (N=7)




Figure C.3.5. Results of (left) replicate and (right) duplicate measurements during the cruise against (a) station number, (b) pressure and (c) concentration of dissolved oxygen. Green line denotes the average of the measurements. Bottom panels (d) show histogram of the measurements.

(7.2) Mutual comparison between each standard KIO₃ solution

During the cruise, mutual comparison between different lots of standard KIO₃ solution was performed to confirm the accuracy of our oxygen measurement and the bias of a standard KIO₃ solution. A concentration of the standard KIO₃ solution “20161025-1” was determined using Na₂S₂O₃ solution standardized with the KIO₃ solution “20161018-1”, and the difference between measurement value and theoretical one. A good agreement among two standards confirmed that there was no systematic shift in our oxygen measurements during the cruise (Figure C.3.6).




Figure C.3.6. Result of mutual comparison of standard KIO₃ solutions during the cruise. Circles and error bars show mean of the measurement value and its uncertainty ($k=2$), respectively. Thick and dashed lines in blue denote the mean and 2 times of standard deviations, respectively, for the measurement through the cruise. Green thin line and light green thick line denote nominal concentration and its uncertainty ($k=2$) of standard KIO₃ solution “20161025-1”.

(7.3) Quality control flag assignment

Quality flag value was assigned to oxygen measurements as shown in Table C.3.3, using the code defined in IOCCP Report No.14 (Swift, 2010).

Table C.3.3. Summary of assigned quality control flags.

Flag	Definition	Number of samples
2	Good	1447
3	Questionable	48
4	Bad (Faulty)	10
5	Not reported	1
6	Replicate measurements	175
Total number of samples		1681

(8) Uncertainty

The repeatability of measurements was evaluated from replicate and duplicate analyses as shown in section (7.1), respectively. Additionally, oxygen measurement involved various uncertainties; precision of glass bottles volume, precision of burette discharge, precision of pickling reagents discharge, determination of reagent blank, standardization of $\text{Na}_2\text{S}_2\text{O}_3$ solution, and concentration of KIO_3 solutions. Considering evaluable uncertainties as above, the standard uncertainty of bottle oxygen concentration ($T=20$, $S=34.5$) was estimated as shown in Table C.3.4. However, it is impossible to determine the accurate uncertainty because there is no reference material for oxygen measurement.

Table C.3.4. Expanded uncertainty ($k=2$) of bottle oxygen in the cruise.

O ₂ conc. ($\mu\text{mol kg}^{-1}$)	Uncertainty ($\mu\text{mol kg}^{-1}$)
20	0.38
30	0.39
50	0.41
70	0.43
100	0.47
150	0.57
200	0.68
250	0.80
300	0.93
400	1.19

Appendix

A1. Methods

(A1.1) Seawater sampling

Following procedure is based on a determination method in IOCCP Report (Langdon, 2010). Seawater samples were collected from 10-liters Niskin bottles attached the CTD-system and a stainless steel bucket for the surface. Seawater for bottle oxygen measurement was transferred from the Niskin bottle and a stainless steel bucket to a volumetrically calibrated dry glass bottles. At least three times the glass volume water was overflowed. Then, pickling reagent-I 1 mL and reagent-II 1mL were added immediately, and sample temperature was measured using a thermometer. After a stopper was inserted carefully into the glass, it was shaken vigorously to mix the content and to disperse the precipitate finely. After the precipitate has settled at least halfway down the glass, the glass was shaken again. The sample glasses containing pickled samples were stored in a laboratory until they were titrated. To prevent air from entering the glass, deionized water (DW) was added to its neck after sampling.

(A1.2) Sample measurement

At least 15 minutes after the re-shaking, the samples were measured on board. Added 1 mL H_2SO_4 solution and a magnetic stirrer bar into the sample glass, samples were titrated with $\text{Na}_2\text{S}_2\text{O}_3$ solution whose molarity was determined with KIO_3 solution. During the titration, the absorbance of iodine in the solution was monitored using a detector. Also, temperature of $\text{Na}_2\text{S}_2\text{O}_3$ solution during the titration was recorded using a thermometer. Dissolved oxygen concentration ($\mu\text{mol kg}^{-1}$) was calculated from sample temperature at the fixation, CTD salinity, glass volume, and titrated volume of the $\text{Na}_2\text{S}_2\text{O}_3$ solution, and oxygen in the pickling reagents-I (1 mL) and II (1 mL) (7.6×10^{-8} mol; Murray *et al.*, 1968).

A2. Reagents recipes

Pickling reagent-I; Manganous chloride solution (3 mol L^{-1})

Dissolve 600 g of $\text{MnCl}_2 \cdot 4\text{H}_2\text{O}$ in DW, then dilute the solution with DW to a final volume of 1 L.

Pickling reagent-II; Sodium hydroxide (8 mol L^{-1}) / sodium iodide solution (4 mol L^{-1})

Dissolve 320 g of NaOH in about 500 mL of DW, allow to cool, then add 600 g NaI and dilute with DW to a final volume of 1 L.

H_2SO_4 solution; Sulfuric acid solution (5 mol L^{-1})

Slowly add 280 mL concentrated H_2SO_4 to roughly 500 mL of DW. After cooling the final volume should be 1 L.

$\text{Na}_2\text{S}_2\text{O}_3$ solution; Sodium thiosulfate solution (0.04 mol L^{-1})

Dissolve 50 g of $\text{Na}_2\text{S}_2\text{O}_3 \cdot 5\text{H}_2\text{O}$ and 0.4 g of Na_2CO_3 in DW, then dilute the solution with DW to a final volume of 5 L.

KIO_3 solution; Potassium iodate solution ($0.001667 \text{ mol L}^{-1}$)

Dry high purity KIO_3 for two hours in an oven at $130\text{ }^\circ\text{C}$. After weight out accurately KIO_3 , dissolve it in DW in a 5 L flask. Concentration of potassium iodate is determined by a gravimetric method.

A3. Other blanks in oxygen measurement

(A3.1) Blank associated with oxidants or reductants in the reagents

The blank $V_{\text{reg-blk}}$, associated with oxidants or reductants in the reagent, was determined as follows. Using a calibrated pipette, 1 mL of the standard KIO_3 solution and 100 mL of DW were added to two glasses each. Then, 1 mL H_2SO_4 solution, 1 mL of pickling reagent-II and 1 mL reagent-I were added in sequence into the first glass. Next, added two times volume of the reagents (2 mL of H_2SO_4 solution, pickling reagent-II and I each) into the second one. After that, the sample was titrated to the end-point with $\text{Na}_2\text{S}_2\text{O}_3$ solution. $V_{\text{reg-blk}}$ was determined with difference of titrated volume of $\text{Na}_2\text{S}_2\text{O}_3$ between the first (total reagents volume is 3 mL) and the second (total reagents volume is 6 mL) one, also, experiments for three times and four times volume of them were carried out. The results are shown in Figure C.3.A1.




Figure C.3.A1. Blank (mL) due to redox species other than oxygen in the reagents.

The relation between difference of the titrant volume and the reagents of the volume (V_{reg}) is expressed as follows;

$$\text{Difference of the titrant volume} = -0.0012 V_{\text{reg}}. \quad (\text{C3.A1})$$

Therefore, $V_{\text{reg-blk}}$ was estimated to be +0.004 mL.

(A3.2) Seawater blank

Blank due to redox species other than oxygen in seawater ($V_{\text{sw-blk}}$) can be a potential source of measurement error. Total blank ($V_{\text{tot-blk}}$) in seawater measurement can be represented as follows;

$$V_{\text{tot-blk}} = V_{\text{blk}} + V_{\text{sw-blk}}. \quad (\text{C3.A1})$$

Because the reagent blank (V_{blk}) determined for pure water is expected to be equal to that in seawater, the difference between blanks for seawater ($V_{\text{tot-blk}}$) and for pure water (V_{blk}) gives the $V_{\text{sw-blk}}$.

Here, $V_{\text{sw-blk}}$ was determined by following procedure. Seawater was collected in the calibrated volumetric glass without the pickling solution. Then 1 mL of the standard KIO_3 solution, H_2SO_4 solution, and reagent solution-II and I each were added in sequence into the glass. After that, the sample was titrated to the end-point by $\text{Na}_2\text{S}_2\text{O}_3$ solution. Similarly, a glass contained 100 mL of DW added with 1 mL of the standard KIO_3 solution, H_2SO_4 solution, pickling reagent solution-II and I were titrated with $\text{Na}_2\text{S}_2\text{O}_3$ solution. The difference of the titrant volume of the seawater and DW glasses gave $V_{\text{sw-blk}}$.

The seawater blank has been reported from 0.4 to 0.8 $\mu\text{mol kg}^{-1}$ in the previous study (Culberson *et al.*, 1991). Additionally, these errors are expected to be the same to all investigators and not to affect the comparison of results from different investigators (Culberson, 1994). However, the magnitude and variability of the seawater blank have not yet been documented. Understanding of the magnitude and variability is important to improve traceability and comparability in oxygen concentration. The determined seawater blanks are shown in Table C.3.A1.

Table C.3.A1. Results of the sample blank determinations.

Station: RF6054 42°-00'N/165°-00'E		Station: RF6074 29°-00'N/165°-00'E	
Depth	Blank	Depth	Blank
(m)	($\mu\text{mol kg}^{-1}$)	(m)	($\mu\text{mol kg}^{-1}$)
26	0.98	51	0.62
250	0.85	504	0.68
771	0.61	1201	0.72
771	0.67	1201	0.58
871	0.64	1601	0.61
1531	0.80	2402	0.59
2129	0.63	2998	0.69
2929	0.80	4001	0.62
3669	0.75	4752	0.71
3669	0.79	4752	0.65
4421	0.75	5500	0.67
4860	0.85	5828	0.77

Reference

- Culberson, A.H. (1994), Dissolved oxygen, in WHPO Pub. 91-1 Rev. 1, November 1994, Woods Hole, Mass., USA.
- Culberson, A.H., G. Knapp, M.C. Stalcup, R.T. Williams, and F. Zemlyak (1991), A comparison of methods for the determination of dissolved oxygen in seawater, WHPO Pub. 91-2, August 1991, Woods Hole, Mass., USA.
- DOE (1994), Handbook of methods for the analysis of the various parameters of the carbon dioxide system in sea water; version 2. *A. G. Dickson and C. Goyet (eds), ORNL/CDIAC-74.*
- Langdon, C. (2010), Determination of dissolved oxygen in seawater by Winkler titration using the amperometric technique, *IOCCP Report No.14, ICPO Pub. 134, 2010 ver.1*
- Murray, C. N., J. P. Riley and T. R. S. Wilson (1968), The solubility of oxygen in Winkler reagents used for the determination of dissolved oxygen. *Deep-Sea Res.* 15, 237–238.
- Swift, J. H. (2010), Reference-quality water sample data: Notes on acquisition, record keeping, and evaluation. *IOCCP Report No.14, ICPO Pub. 134, 2010 ver.1.*

4. Nutrients

10 June 2020

(1) Personnel

Hiroyuki HATAKEYAMA (GEMD/JMA)

Daisuke SASANO (GEMD/JMA)

Kei KONDO (GEMD/JMA)

Satomi TANAKA (GEMD/JMA)

Rie SANAI (GEMD/JMA)

(2) Station occupied

A total of 46 stations (Leg 1: 26, Leg 2: 20) were occupied for nutrients measurements. Station location and sampling layers of nutrients are shown in Figures C.4.1 and C.4.2.




Figure C.4.1. Location of observation stations of nutrients. Closed and open circles indicate sampling and no-sampling stations, respectively.




Figure C.4.2. Distance-depth distributions of sampling layers of nutrients.

(3) Instrument

The nutrients analysis was carried out on 4-channel Auto Analyzer III (BL TEC K.K., Japan) for 4 parameters; nitrate+nitrite, nitrite, phosphate, and silicate.

(4) Sampling and measurement

Methods of seawater sampling, measurement, and data processing of nutrient concentration were described in Appendixes A1, A2, and A3, respectively. The reagents for the measurement were prepared according to recipes shown in Appendix A4.

(5) Nutrients standards

(5.1) Volumetric laboratory ware of in-house standards

All volumetric wares were gravimetrically calibrated. The weights obtained in the calibration weighing were corrected for the density of water and for air buoyancy. Polymethylpenten volumetric flasks were gravimetrically calibrated at the temperature of use within 4–6 °C. All pipettes have nominal calibration tolerances of 0.1 % or better. These were gravimetrically calibrated in order to verify and improve upon this nominal tolerance.

(5.2) Reagents of standard

The batches of the reagents used for standard are listed in Table C.4.1.

Table C.4.1. List of reagents of standard used in the cruise.

	Name	CAS No	Lot. No	Industries
Nitrate	potassium nitrate 99.995 suprapur®	7757-79-1	B0993065	Merck KGaA
Nitrite	sodium nitrite GR for analysis ACS, Reag. Ph Eur	7632-00-0	A0723349	Merck KGaA
Phosphate	potassium dihydrogen phosphate anhydrous 99.995 suprapur®	7778-77-0	B1144508	Merck KGaA
Silicate	Silicon standard solution 1000 mg/l Si*	-	HC54715536	Merck KGaA

* Traceable to NIST-SRM3150

(5.3) Low nutrient seawater (LNSW)

Surface water with sufficiently low nutrient concentration was taken and filtered using 10 µm pore size membrane filter in our previous cruise. This water was stored in 20 liter flexible container with paper box.

(5.4) In-house standard solutions

Nutrient concentrations for A, B and C standards were set as shown in Table C.4.2. A and B standards were prepared with deionized water (DW). C standard (full scale of working standard) was mixture of B-1 and B-2 standards, and was prepared with LNSW. C-1 standard, whose concentrations of nutrient were nearly zero, was prepared as LNSW slightly added with DW to be equal with mixing ratio of LNSW and DW in C standard. The C-2 to -5 standards were prepared with mixture of C-1 and C standards in stages as 1/4, 2/4, 3/4, and 4/4 (i.e., pure “C standard”) concentration for full scale, respectively. The actual concentration of nutrients in each standard was calculated based on the solution temperature and factors of volumetric laboratory wares calibrated prior to use. Nominal zero concentration of nutrient was determined in measurement of DW after refraction error correction. The calibration curves for each run were obtained using 5 levels of C-1 to -5 standards. These standard solutions were periodically renewed as shown in Table C.4.3.

Table C.4.2. Nominal concentrations of nutrients for A, B, and C standards at 20 °C. Unit is $\mu\text{mol L}^{-1}$.

	A	B	C
Nitrate	27500	573	45.7
Nitrite	12500	250	2.0
Phosphate	2120	43.6	3.48
Silicate	35780	2318	185

Table C.4.3. Schedule of renewal of in-house standards.

Standard	Renewal
A-1 std. (NO_3)	No renewal
A-2 std. (NO_2)	No renewal
A-3 std. (PO_4)	No renewal
A-4 std. (Si)	Commercial prepared solution
B-1 std. (mixture of A-1, A-3, and A-4 stds.)	Maximum 8 days
B-2 std. (diluted A-2 std.)	Maximum 15 days
C-std. (mixture of B-1 and B-2 stds.)	Every measurement
C-1 to -5 stds.	Every measurement

(6) Certified reference material

Certified reference material for nutrients in seawater (hereafter CRM), which was prepared by the General Environmental Technos (KANSO Technos, Japan), was used every analysis at each hydrographic station. Using CRMs for the analysis of seawater, stable comparability and uncertainty of our data are secured.

CRMs used in the cruise are shown in Table C.4.4.

Table C.4.4. Certified concentration and uncertainty ($k=2$) of CRMs. Unit is $\mu\text{mol kg}^{-1}$.

	Nitrate	Nitrite	Phosphate	Silicate
CRM-BY	0.024±0.019*	0.019±0.0085*	0.039±0.010*	1.763±0.063
CRM-BW	24.59±0.20	0.067±0.010	1.541±0.014	60.01±0.42
CRM-CB	35.79±0.27	0.116±0.0057	2.520±0.022	109.2±0.62
CRM-BZ	43.35±0.33	0.215±0.011	3.056±0.033	161.0±0.93

* Reference value because concentration is under limit of quantitation

The CRM-BY and -CB were analyzed every runs using newly opened CRM bottle at each hydrographic station. The CRM-BW and -BZ were also analyzed every runs but were newly opened every 2 or 3 runs. Although this usage of CRM might be less common, we have confirmed a stability of the opened CRM bottles to be tolerance in our observation. The CRM bottles were stored at a laboratory in the ship, where the temperature was maintained around 25 °C.

It is noted that nutrient data in our report are calibrated not on CRM but on in-house standard solutions. Therefore, to calculate data based on CRM, it is necessary that values of nutrient concentration in our report are correlated with CRM values measured in the same analysis run. The result of CRM measurements is attached as 49UP20170623_P13N_nut_CRM_measurement.csv.

(7) Quality Control

(7.1) Replicate and duplicate analyses

We took replicate (pair of water samples taken from a single Niskin bottle) and duplicate (pair of water samples taken from different Niskin bottles closed at the same depth) samples of nutrient through the cruise. Results of the analyses are summarized in Table C.4.5. Detailed results of them are shown in Figures C.4.3–C.4.5. The calculation of the standard deviation from the difference of sets was based on a procedure (SOP 23) in DOE (1994).

Table C.4.5. Average and standard deviation of difference of replicate and duplicate measurements through the cruise. Unit is $\mu\text{mol kg}^{-1}$.

Measurement	Nitrate+nitrite	Phosphate	Silicate
Replicate	0.019 ± 0.019 (N=181)	0.002 ± 0.002 (N=175)	0.106 ± 0.102 (N=181)
Duplicate	0.016 ± 0.014 (N=11)	0.004 ± 0.004 (N=9)	0.135 ± 0.123 (N=11)




Figure C.4.3. Result of (left) replicate and (right) duplicate measurements of nitrate+nitrite through the cruise versus (a) station number, (b) sampling pressure, (c) concentration, and (d) histogram of the measurements. Green line indicates the mean of the differences of concentration of replicate/duplicate analyses.




Figure C.4.4. Same as Figure C.4.3 but for phosphate.




Figure C.4.5. Same as Figure C.4.3 but for silicate.

(7.2) Measurement of CRMs

CRM measurements during the cruise are summarized in Table C.4.6, whose concentrations were assigned with in-house standard solutions. The measured concentrations of CRM-BZ through the cruise are shown in Figures C.4.6–C.4.9.

Table C.4.6. Summary of (upper) mean concentration and its standard deviation (unit: $\mu\text{mol kg}^{-1}$), (middle) coefficient of variation (%), and (lower) total number of CRMs measurements through the cruise.

	Nitrate+nitrite	Nitrite	Phosphate	Silicate
	0.088 ± 0.018	0.026 ± 0.002	0.038 ± 0.007	1.76 ± 0.06
CRM-BY	20.33%	7.18%	18.59%	3.27%
	(N=91)	(N=91)	(N=87)	(N=91)
	24.69 ± 0.05	0.076 ± 0.002	1.54 ± 0.01	59.83 ± 0.14
CRM-BW	0.20%	2.24%	0.44%	0.23%
	(N=67)	(N=67)	(N=65)	(N=67)
	35.96 ± 0.06	0.127 ± 0.003	2.52 ± 0.01	109.20 ± 0.20
CRM-CB	0.18%	2.09%	0.32%	0.19%
	(N=91)	(N=91)	(N=88)	(N=91)
	43.65 ± 0.07	0.223 ± 0.005	3.06 ± 0.01	160.78 ± 0.29
CRM-BZ	0.17%	2.03%	0.18%	0.18%
	(N=68)	(N=68)	(N=66)	(N=68)




Figure C.4.6. Time-series of measured concentration of nitrate+nitrite of CRM-BZ through the cruise. Closed and open circles indicate the newly and previously opened bottle, respectively. Thick and dashed lines denote the mean and 2 times of standard deviations of the measurements through the cruise, respectively.




Figure C.4.7. Same as Figure C.4.6 but for nitrite.




Figure C.4.8. Same as Figure C.4.6 but for phosphate.




Figure C.4.9. Same as Figure C.4.6 but for silicate.

(7.3) Precision of analysis in a run

To monitor precision of analysis, the same samples were repeatedly measured in a sample array in a run. For this, C-5 standard solutions were randomly arrayed in every 2–10 samples as “check standard” (the number of the standard is about 8–9) in the run. The precision was estimated as coefficient of variation of the measurements. The results are summarized in Table C.4.7. The time series are shown in Figures C.4.10–C.4.13.




Figure C.4.10. Time-series of coefficient of variation of “check standard” measurement of nitrate+nitrite through the cruise. Thick and dashed lines denote the mean and 2 times of standard deviations of the measurements through the cruise, respectively.




Figure C.4.11. Same as Figure C.4.10 but for nitrite.




Figure C.4.12. Same as Figure C.4.10 but for phosphate.




Figure C.4.13. Same as Figure C.4.10 but for silicate.

Table C.4.7. Summary of precisions during the cruise.

	Nitrate+nitrite	Nitrite	Phosphate	Silicate
Median	0.09%	0.10%	0.08%	0.08%
Mean	0.09%	0.10%	0.08%	0.10%
Minimum	0.03%	0.04%	0.02%	0.04%
Maximum	0.20%	0.16%	0.21%	0.23%
Number	46	46	46	46

(7.4) Carryover

Carryover coefficients were determined in each analysis run, using C-5 standard (high standard) followed by two C-1 standards (low standard). Time series of the carryover coefficients are shown in Figures C.4.14–17.




Figure C.4.14. Time-series of carryover coefficients in measurement of nitrate+nitrite through the cruise.




Figure C.4.15. Same as Figure C.4.14 but for nitrite.




Figure C.4.16. Same as Figure C.4.14 but for phosphate.




Figure C.4.17. Same as Figure C.4.14 but for silicate.

(7.5) Limit of detection/quantitation of measurement

Limit of detection (LOD) and quantitation (LOQ) of nutrient measurement were estimated from standard deviation (σ) of repeated measurements of nutrients concentration in C-1 standard as 3σ and 10σ , respectively. Summary of LOD and LOQ are shown in Table C.4.8.

Table C.4.8. Limit of detection (LOD) and quantitation (LOQ) of nutrient measurement in the cruise. Unit is $\mu\text{mol kg}^{-1}$.

	LOD	LOQ
Nitrate+nitrite	0.048	0.159
Nitrite	0.002	0.006
Phosphate	0.008	0.028
Silicate	0.062	0.207

(7.6) Quality control flag assignment

Quality flag value was assigned to nutriment measurements as shown in Table C.4.9, using the code defined in IOCCP Report No.14 (Swift, 2010).

Table C.4.9. Summary of assigned quality control flags.

Flag	Definition	Nitrate+nitrite	Nitrite	Phosphate	Silicate
2	Good	1495	1488	1456	1496
3	Questionable	1	9	5	0
4	Bad (Faulty)	4	4	45	4
5	Not reported	0	0	0	0
6	Replicate measurements	181	180	175	181
Total number of samples		1681	1681	1681	1681

(8) Uncertainty

(8.1) Uncertainty associated with concentration level: U_c

Generally, an uncertainty of nutrient measurement is expressed as a function of its concentration level which reflects that some components of uncertainty are relatively large in low concentration. Empirically, the uncertainty associated with concentrations level (U_c) can be expressed as follows;

$$\sqrt{U_c (\%)} = a + b \cdot (1/C_x) + c \cdot (1/C_x)^2, \quad (C4.1)$$

where C_x is the concentration of sample for parameter X.

Using the coefficients of variation of the CRM measurements throughout the cruise, uncertainty associated with concentrations of nitrate+nitrite, phosphate, and silicate were determined as follows:

$$U_{c-no3} (\%) = 0.138 + 1.449 \times (1/C_n) + 0.030 \times (1/C_n)^2 \quad (C4.2)$$

$$U_{c-po4} (\%) = -0.011 + 0.711 \times (1/C_p) \quad (C4.3)$$

$$U_{c-sil} (\%) = 0.147 + 4.798 \times (1/C_s) + 1.187 \times (1/C_s)^2, \quad (C4.4)$$

where C_n , C_p , and C_s represent concentrations of nitrate+nitrite, phosphate, and silicate, respectively, in $\mu\text{mol kg}^{-1}$. Figures C.4.18–C.4.20 show the calculated uncertainty graphically.




Figure C.4.18. Uncertainty of nitrate + nitrite associated with concentration level.




Figure C.4.19. Same as Figure C.4.18 but for phosphate.




Figure C.4.20. Same as Figure C.4.18 but for silicate.

(8.2) Uncertainty of analysis between runs: U_s

Uncertainty of analysis among runs (U_s) was evaluated based on the coefficient of variation of measured concentrations of CRM-BZ with high concentration among the CRM lots throughout the cruise, as shown in subsection (7.2). The reason for using the CRM lot BZ to state U_s is to exclude the effect of uncertainty associated with lower concentration described previously. As is clear from the definition of U_c , U_s is equal to U_c at nutrients concentrations of lot BZ. It is important to note that U_s includes all of uncertainties during the measurements throughout stations, namely uncertainties of concentrations of in-house standard solutions prepared for each run, uncertainties of slopes and intercepts of the calibration curve in each

run if first order calibration curve applied, precision of measurement in a run (U_a), and between-bottle homogeneity of the CRM.

(8.3) Uncertainty of analysis in a run: U_a

Uncertainty of analysis in a run (U_a) was evaluated based on the coefficient of variation of repeated measurements of the “check standard” solution, as shown in subsection (7.3). The U_a reflects the conditions associated with chemistry of colorimetric measurement of nutrients, and stability of electronic and optical parts of the instrument throughout a run. Under a well-controlled condition of the measurements, U_a might show Poisson distribution with a mean as shown in Figures C.4.10–C.4.13 and Table C.4.7 and treated as a precision of measurement. U_a is a part of U_c at the concentration as stated in a previous section for U_c .

However, U_a may show larger value which was not expected from Poisson distribution of U_a due to the malfunction of the instruments, larger ambient temperature change, human errors in handling samples and chemistries and contaminations of samples in a run. In the cruise, we observed that U_a of our measurement was usually small and well-controlled in most runs as shown in Figures C.4.10–C.4.13 and Table C.4.7. However, in a few runs, U_a showed high values which were over the mean \pm twice the standard deviations of U_a , suggesting that the measurement system might have some problems.

(8.4) Uncertainty of CRM concentration: U_r

In the certification of CRM, the uncertainty of CRM concentrations (U_r) was stated by the manufacturer (Table C.4.4) as expanded uncertainty at $k=2$. This expanded uncertainty reflects the uncertainty of the Japan Calibration Service System (JCSS) solutions, characterization in assignment, between-bottle homogeneity, and long term stability. We have ensured comparability between cruises by ensuring that at least two lots of CRMs overlap between cruises. In comparison of nutrient concentrations between cruises using KANSO CRMs in an organization, it was not necessary to include U_r in the conclusive uncertainty of concentration of measured samples because comparability of measurements was ensured in an organization as stated previously.

(8.5) Conclusive uncertainty of nutrient measurements of samples: U

To determine the conclusive uncertainty of nutrient measurements of samples (U), we use two functions depending on U_a value acquired at each run as follows:

When U_a was small and measurement was well-controlled condition, the conclusive uncertainty of nutrient measurements of samples, U , might be as below:

$$\sqrt{U} = U_c \quad (C4.5)$$

When U_a was relative large and the measurement might have some problems, the conclusive uncertainty of nutrient measurements of samples, U , can be expanded as below:

$$U = \sqrt{U_c^2 + U_a^2} \quad (C4.6)$$

When U_a was relative large and the measurement might have some problems, the equation of U is defined as to include U_a to evaluate U , although U_a partly overlaps with U_c . It means that the equation overestimates the conclusive uncertainty of samples. On the other hand, for low concentration there is a possibility that the equation not only overestimates but also underestimates the conclusive uncertainty because the functional shape of U_c in lower concentration might not be the same and cannot be verified. However, we believe that the applying the above function might be better way to evaluate the conclusive uncertainty of nutrient measurements of samples because we can do realistic evaluation of uncertainties of nutrient concentrations of samples which were obtained under relatively unstable conditions, larger U_a as well as the evaluation of them under normal and good conditions of measurements of nutrients.

Appendix

A1. Seawater sampling

Seawater samples were collected from 10-liters Niskin bottle attached CTD-system and a stainless steel bucket for the surface. Samples were drawn into 10 mL polymethylpenten vials using sample drawing tubes. The vials were rinsed three times before water filling and were capped immediately after the drawing.

No transfer was made and the vials were set on an auto sampler tray directly. Samples were analyzed immediately after collection.

A2. Measurement

(A2.1) General

Auto Analyzer III is based on Continuous Flow Analysis method and consists of sampler, pump, manifolds, and colorimeters. As a baseline, we used artificial seawater (ASW).

(A2.2) Nitrate+nitrite and nitrite

Nitrate+nitrite and nitrite were analyzed according to the modification method of Armstrong (1967). The sample nitrate was reduced to nitrite in a glass tube which was filled with granular cadmium coated with copper. The sample stream with its equivalent nitrite was treated with an acidic, sulfanilamide reagent and the nitrite forms nitrous acid which reacts with the sulfanilamide to produce a diazonium ion. N-1-naphthylethylene-diamine was added to the sample stream then coupled with the diazonium ion to produce a red, azo dye. With reduction of the nitrate to nitrite, sum of nitrate and nitrite were measured; without reduction, only nitrite was measured. Thus, for the nitrite analysis, no reduction was performed and the alkaline buffer was not necessary. The flow diagrams for each parameter are shown in Figures C.4.A1 and C.4.A2. If the reduction efficiency of the cadmium column became lower than 95 %, the column was replaced.




Figure C.4.A1. Nitrate+nitrite (ch. 1) flow diagram.




Figure C.4.A2. Nitrite (ch. 2) flow diagram.

(A2.3) Phosphate

The phosphate analysis was a modification of the procedure of Murphy and Riley (1962). Molybdic acid was added to the seawater sample to form phosphomolybdic acid which was in turn reduced to phosphomolybdous acid using L-ascorbic acid as the reductant. The flow diagram for phosphate is shown in Figure C.4.A3.




Figure C.4.A3. Phosphate (ch. 3) flow diagram.

(A2.4) Silicate

The silicate was analyzed according to the modification method of Grasshoff *et al.* (1983), wherein silicomolybdic acid was first formed from the silicate in the sample and added molybdic acid, then the silicomolybdic acid was reduced to silicomolybdous acid, or "molybdenum blue," using L-ascorbic acid as the reductant. The flow diagram for silicate is shown in Figure C.4.A4.




Figure C.4.A4. Silicate (ch. 4) flow diagram.

A3. Data processing

Raw data from Auto Analyzer III were recorded at 1-second interval and were treated as follows;

- Check the shape of each peak and position of peak values taken, and then change the positions of peak values taken if necessary.
- Baseline correction was done basically using liner regression.
- Reagent blank correction was done basically using liner regression.
- Carryover correction was applied to peak heights of each sample.
- Sensitivity correction was applied to peak heights of each sample.
- Refraction error correction was applied to peak heights of each seawater sample.
- Calibration curves to get nutrients concentration were assumed quadratic expression.
- Concentrations were converted from $\mu\text{mol L}^{-1}$ to $\mu\text{mol kg}^{-1}$ using seawater density.

A4. Reagents recipes

(A4.1) Nitrate+nitrite

Ammonium chloride (buffer), $0.7 \mu\text{mol L}^{-1}$ (0.04 % w/v);

Dissolve 190 g ammonium chloride, NH_4Cl , in ca. 5 L of DW, add about 5 mL ammonia(aq) to adjust pH of 8.2–8.5.

Sulfanilamide, $0.06 \mu\text{mol L}^{-1}$ (1 % w/v);

Dissolve 5 g sulfanilamide, $4\text{-NH}_2\text{C}_6\text{H}_4\text{SO}_3\text{H}$, in 430 mL DW, add 70 mL concentrated HCl. After mixing, add 1 mL Brij-35 (22 % w/w).

N-1-naphtylethylene-diamine dihydrochloride (NEDA), $0.004 \mu\text{mol L}^{-1}$ (0.1 % w/v);

Dissolve 0.5 g NEDA, $\text{C}_{10}\text{H}_7\text{NH}_2\text{CH}_2\text{CH}_2\text{NH}_2 \cdot 2\text{HCl}$, in 500 mL DW.

(A4.2) Nitrite

Sulfanilamide, $0.06 \mu\text{mol L}^{-1}$ (1 % w/v); Shared from nitrate reagent.

N-1-naphtylethylene-diamine dihydrochloride (NEDA), $0.004 \mu\text{mol L}^{-1}$ (0.1 % w/v); Shared from nitrate reagent.

(A4.3) Phosphate

Ammonium molybdate, $0.005 \mu\text{mol L}^{-1}$ (0.6 % w/v);

Dissolve 3 g ammonium molybdate(VI) tetrahydrate, $(\text{NH}_4)_6\text{Mo}_7\text{O}_{24} \cdot 4\text{H}_2\text{O}$, and 0.05 g potassium antimonyl tartrate, $\text{C}_8\text{H}_4\text{K}_2\text{O}_{12}\text{Sb}_2 \cdot 3\text{H}_2\text{O}$, in 400 mL DW and add 40 mL concentrated H_2SO_4 . After mixing, dilute the solution with DW to final volume of 500 mL and add 2 mL sodium dodecyl sulfate (15 % solution in water).

L(+)-ascorbic acid, $0.08 \mu\text{mol L}^{-1}$ (1.5 % w/v);

Dissolve 4.5 g L(+)-ascorbic acid, $\text{C}_6\text{H}_8\text{O}_6$, in 300 mL DW. After mixing, add 10 mL acetone. This reagent was freshly prepared before every measurement.

(A4.4) Silicate

Ammonium molybdate, $0.005 \mu\text{mol L}^{-1}$ (0.6 % w/v);

Dissolve 3 g ammonium molybdate(VI) tetrahydrate, $(\text{NH}_4)_6\text{Mo}_7\text{O}_{24} \cdot 4\text{H}_2\text{O}$, in 500 mL DW and added concentrated 2 mL H_2SO_4 . After mixing, add 2 mL sodium dodecyl sulfate (15 % solution in water).

Oxalic acid, $0.4 \mu\text{mol L}^{-1}$ (5 % w/v);

Dissolve 25 g oxalic acid dihydrate, $(\text{COOH})_2 \cdot 2\text{H}_2\text{O}$, in 500 mL DW.

L(+)-ascorbic acid, $0.08 \mu\text{mol L}^{-1}$ (1.5 % w/v); Shared from phosphate reagent.

(A4.5) Baseline

Artificial seawater (salinity is ~34.7);

Dissolve 160.6 g sodium chloride, NaCl , 35.6 g magnesium sulfate heptahydrate, $\text{MgSO}_4 \cdot 7\text{H}_2\text{O}$, and 0.84 g sodium hydrogen carbonate, NaHCO_3 , in 5 L DW.

References

- Armstrong, F. A. J., C. R. Stearns and J. D. H. Strickland (1967), The measurement of upwelling and subsequent biological processes by means of the Technicon TM Autoanalyzer TM and associated equipment, *Deep-Sea Res.*, 14(3), 381–389.
- DOE (1994), Handbook of methods for the analysis of the various parameters of the carbon dioxide system in sea water; version 2. *A. G. Dickson and C. Goyet (eds), ORNL/CDIAC-74.*
- Grasshoff, K., Ehrhardt, M., Kremling K. et al. (1983), Methods of seawater analysis. 2nd rev, *Weinheim: Verlag Chemie, Germany, West.*
- Murphy, J. and Riley, J.P. (1962), *Analytica chimica Acta*, 27, 31-36.
- Swift, J. H. (2010), Reference-quality water sample data: Notes on acquisition, record keeping, and evaluation. *IOCCP Report No.14, ICPO Pub. 134, 2010 ver.1.*

5. *Phytopigments (chlorophyll-*a* and phaeopigment)*

8 June 2020

(1) Personnel

Hiroyuki HATAKEYAMA (GEMD/JMA)

Kei KONDO (GEMD/JMA)

(2) Station occupied

A total of 40 stations (Leg 1: 26, Leg 2: 14) were occupied for phytopigment measurements. Station location and sampling layers of phytopigment are shown in Figures C.5.1 and C.5.2.




Figure C.5.1. Location of observation stations of chlorophyll-*a*. Closed and open circles indicate sampling and no-sampling stations, respectively.




Figure C.5.2. Distance-depth distribution of sampling layers of chlorophyll-*a*.

(3) Reagents

N,N-dimethylformamide (DMF)

Hydrochloric acid (HCl), 0.5 mol L⁻¹

Chlorophyll-*a* standard from *Anacystis nidulans* algae (Sigma-Aldrich, United States)

Rhodamine WT (Turner Designs, United States)

(4) Instruments

Fluorometer: 10-AU (Turner Designs, United States)

Spectrophotometer: UV-1800 (Shimadzu, Japan)

(5) Standardization

(5.1) Determination of chlorophyll-*a* concentration of standard solution

To prepare the pure chlorophyll-*a* standard solution, reagent powder of chlorophyll-*a* standard was dissolved in DMF. A concentration of the chlorophyll-*a* solution was determined with the spectrophotometer as follows:

$$\text{chl } a \text{ concentration } (\mu\text{g mL}^{-1}) = A_{\text{chl}} / a_{\text{phy}}^* \quad (\text{C5.1})$$

where A_{chl} is the difference between absorbance at 663.8 nm and 750 nm, and a_{phy}^* is specific absorption coefficient (UNESCO, 1994). The specific absorption coefficient is 88.74 L g⁻¹ cm⁻¹ (Porra *et al.*, 1989).

(5.2) Determination of R and f_{ph}

Before measurements, sensitivity of the fluorometer was calibrated with pure DMF and a rhodamine 1 ppm solution (diluted with deionized water).

The chlorophyll-*a* standard solution, whose concentration was precisely determined in subsection (5.1), was measured with the fluorometer, and after acidified with 1–2 drops 0.5 mol L⁻¹ HCl the solution was also measured. The acidification coefficient (R) of the fluorometer was also calculated as the ratio of the unacidified and acidified readings of chlorophyll-*a* standard solution. The linear calibration factor (f_{ph}) of the fluorometer was calculated as the slope of the acidified reading against chlorophyll-*a* concentration. The R and f_{ph} in the cruise are shown in Table C.9.1.

Table C.9.1. R and f_{ph} in the cruise.

Acidification coefficient (R)	1.903
Linear calibration factor (f_{ph})	6.1121

(6) Seawater sampling and measurement

Water samples were collected from 10-liters Niskin bottle attached the CTD-system and a stainless steel bucket for the surface. A 200 mL seawater sample was immediately filtered through 25 mm GF/F filters by low vacuum pressure below 15 cmHg, the particulate matter collected on the filter. Phytopigments were extracted in vial with 9 mL of DMF. The extracts were stored for 24 hours in the refrigerator at -30 °C until analysis.

After the extracts were put on the room temperature for at least one hour in the dark, the extracts were decanted from the vial to the cuvette. Fluorometer readings for each cuvette were taken before and after acidification with 1–2 drops 0.5 mol L⁻¹ HCl. Chlorophyll-*a* and phaeopigment concentrations (μg mL⁻¹) in the sample are calculated as follows:

(C5.2)

(C5.3)

F₀: reading before acidification

F_a: reading after acidification

R: acidification coefficient (F₀/F_a) for pure chlorophyll-*a*

f_{ph} : linear calibration factor

v: extraction volume

V: sample volume.

(7) Quality control flag assignment

Quality flag value was assigned to oxygen measurements as shown in Table C.5.2, using the code defined in IOCCP Report No.14 (Swift, 2010).

Table C.5.2 Summary of assigned quality control flags.

Flag	Definition	Chl <i>a</i>	Phaeo.
2	Good	301	301
3	Questionable	0	0
4	Bad (Faulty)	7	7
5	Not reported	1	1
Total number		309	309

References

- Porra, R. J., W. A. Thompson and P. E. Kriedemann (1989), Determination of accurate coefficients and simultaneous equations for assaying chlorophylls *a* and *b* extracted with four different solvents: verification of the concentration of chlorophyll standards by atomic absorption spectroscopy. *Biochem. Biophys. Acta*, 975, 384-394.
- Swift, J. H. (2010), Reference-quality water sample data: Notes on acquisition, record keeping, and evaluation. *IOCCP Report No.14, ICPO Pub. 134, 2010 ver.1*.
- UNESCO (1994), Protocols for the joint global ocean flux study (JGOFS) core measurements: Measurement of chlorophyll *a* and phaeopigments by fluorometric analysis, *IOC manuals and guides 29, Chapter 14*.

6. Total Dissolved Inorganic Carbon (DIC)

30 September 2023

(8) Personnel

SAKAMOTO Naoaki

TANI Masanobu

TANIZAKI Chiho

(9) Station occupied

A total of 38 stations (Leg 1: 24, Leg 2: 14) were occupied for total dissolved inorganic carbon (DIC). Station location and sampling layers of them are shown in Figures C.6.1 and C.6.2, respectively.




Figure C.6.1. Location of observation stations of DIC. Closed and open circles indicate sampling and no-sampling stations, respectively.




Figure C.6.2. Distance-depth distribution of sampling layers of DIC.

(10) Instrument

The measurement of DIC was carried out with DIC/TA analyzers (Nihon ANS Co. Ltd, Japan). We used two analyzers concurrently. These analyzers are designated as apparatus A and B.

(11) Sampling and measurement

Methods of seawater sampling, poisoning, measurement, and calculation of DIC concentrations were based on the Standard Operating Procedure (SOP) described in PICES Special Publication 3, SOP-2 (Dickson et al., 2007). DIC was determined by coulometric analysis (Johnson et al., 1985, 1987) using an automated CO₂ extraction unit and a coulometer. Details of sampling and measurement are shown in Appendix A1.

(12) Calibration

The concentration of DIC (C_T) in moles per kilogram (mol kg⁻¹) of seawater was calculated from the following equation:

$$C_T = N_S / (cV \cdot \rho_S) \quad (C6.1)$$

where N_S is the counts of the coulometer (gC), cV is the calibration factor (gC (mol L⁻¹)⁻¹), and ρ_S is density of seawater (kg L⁻¹), which is calculated from the salinity of the sample and the water temperature of the water-jacket for the sample pipette.

The values of cV were determined by measurements of Certified Reference Materials (CRMs) that were provided by Dr. Andrew G. Dickson of the Scripps Institution of Oceanography. Table C.6.1 provides information about the CRM batches used in this cruise.

Table C.6.1. Certified C_T and standard deviation of CRM. Unit of C_T is $\mu\text{mol kg}^{-1}$. More information is available at the NOAA web site (https://www.ncei.noaa.gov/access/ocean-carbon-acidification-data-system/oceans/Dickson_CRM/batches.html).

Batch number	160
C_T	2030.39 ± 0.36
Salinity	33.414

The CRM measurement was carried out at every station. After the cruise, a value of cV was assigned to each apparatus (A, B). Table C.6.2 summarizes the cV values. Figure C.6.3 shows details.

Table C.6.2. Assigned cV and its standard deviation for each apparatus during the cruise. Unit is $\text{gC (mol L}^{-1})^{-1}$.

Apparatus	cV
A	Leg 1 0.191105 ± 0.000355 (N=53)
	Leg 2 0.191011 ± 0.000227 (N=27)
B	Leg 1 0.197065 ± 0.000269 (N=49)
	Leg 2 0.197229 ± 0.000185 (N=27)




Figure C.6.3. Results of the cV at each station assigned for apparatus (a) A and (b) B. The solid, dashed, and dotted lines denote the mean, the mean \pm twice the S.D., and the mean \pm thrice the S.D. for all measurements, respectively.

The precisions of the cV is equated to its coefficient of variation (= S.D. / mean). They were 0.186 % for apparatus A in Leg 1, 0.119 % for apparatus A in Leg 2, 0.137 % for apparatus B in Leg 1 and 0.094 % for apparatus B in Leg 2. They correspond to $3.77 \mu\text{mol kg}^{-1}$, $2.41 \mu\text{mol kg}^{-1}$, $2.77 \mu\text{mol kg}^{-1}$ and $1.90 \mu\text{mol kg}^{-1}$ in C_T of CRM batch 160, respectively.

Finally, the value of C_T was multiplied by 1.00067 (= $300.2 / 300.0$) to correct dilution effect induced by addition of 0.2 mL of mercury (II) chloride (HgCl_2) solution in a sampling bottle with a volume of ~ 300 mL.

(13) Quality Control

(6.1) Replicate and duplicate analyses

We took replicate (pair of water samples taken from a single Niskin bottle) and duplicate (pair of water samples taken from different Niskin bottles closed at the same depth) samples of DIC throughout the cruise. Table C.6.3 summarizes the results of the measurements with each apparatus. Figures C.6.4–C.6.5 show details of the results. The calculation of the standard deviation from the difference of sets of measurements was based on a procedure (SOP 23) in DOE (1994).

Table C.6.3. Summary of replicate and duplicate measurements. Unit is $\mu\text{mol kg}^{-1}$.

	Apparatus A	Apparatus B
Measurement	Average magnitude of difference \pm S.D.	
Replicate	3.5 ± 3.0 (N=47)	2.1 ± 1.9 (N=56)
Duplicate	1.7 ± 1.4 (N=4)	1.7 ± 1.3 (N=4)




Figure C.6.4. Results of (left) replicate and (right) duplicate measurements during the cruise versus (a) station number, (b) pressure, and (c) C_T determined by apparatus A. The green lines denote the averages of the measurements. The bottom panels (d) show histograms of the measurements.




Figure C.6.5. Same as Figure C.6.4, but for apparatus B.

(6.2) Measurements of CRM and working reference materials

The precision of the measurements was monitored by using the CRMs and working reference

materials bottled in our laboratory (Appendix A2). The CRM (batch 160) and working reference material measurements were carried out at every station. At the beginning of the measurement of each station, we measured a working reference material and a CRM. If the results of these measurements were confirmed to be good, measurements on seawater samples were begun. At the end of a sequence of measurements at a station, another CRM bottle was measured. A CRM measurement was repeated twice from the same bottle. Table C.6.4 summarizes the differences in the repeated measurements of the CRMs, the mean C_T of the CRM measurements, and the mean C_T of the working reference material measurements. Figures C.6.6–C.6.8 show detailed results.

Table C.6.4. Summary of difference and mean of C_T in the repeated measurements of CRM and the mean C_T of the working reference material. These data are based on good measurements. Unit is $\mu\text{mol kg}^{-1}$.

Apparatus	CRM	Working reference material	
	Average magnitude of difference \pm S.D.	Mean Ave. \pm S.D.	Mean Ave. \pm S.D.
A	3.3 ± 2.9 (N=39)	2030.3 ± 2.7 (N=39)	2077.9 ± 3.1 (N=20)
B	1.8 ± 1.5 (N=37)	2030.4 ± 2.3 (N=37)	2077.6 ± 2.2 (N=20)




Figure C.6.6. The absolute difference (R) of C_T in repeated measurements of CRM determined by apparatus (a) A and (b) B. The solid line indicates the average of R (\bar{R}). The dashed and dotted lines denote the upper warning limit ($2.512\bar{R}$) and upper control limit ($3.267\bar{R}$), respectively (see Dickson et al., 2007).




Figure C.6.7. The mean C_T of measurements of CRM. The panels show the results for apparatus (a) A and (b) B. The solid line indicates the mean of the measurements throughout the cruise. The dashed and dotted lines denote the upper/lower warning limit (mean \pm 2S.D.) and the upper/lower control limit (mean \pm 3S.D.), respectively. The gray dashed line denotes certified C_T of CRM.




Figure C.6.8. Calculated C_T of working reference material measured by apparatus (a) A and (b) B. The solid, dashed and dotted lines are the same as in Figure C.6.7.

(6.3) Comparisons with other CRM batches

At every few stations, other CRM batches (155 and 157) were measured to provide comparisons with batch 160 to confirm the determination of C_T in our measurements. For these CRM measurements, C_T was calculated from the cV determined from batch 160 measurement. Figures C.6.9 show the differences between the calculated and certified C_T .




Figure C.6.9. The differences between the calculated C_T from batch 160 measurements and the certified C_T . The panels show the results for apparatus (a) A and (b) B. Colors indicate CRM batches; red: 155 and green: 157

(6.4) Quality control flag assignment

A quality control flag value was assigned to the DIC measurements (Table C.6.5) using the code defined in the IOCCP Report No.14 (Swift, 2010).

Table C.6.5. Summary of assigned quality control flags.

Flag	Definition	Number of samples
2	Good	1256
3	Questionable	38
4	Bad (Faulty)	4
5	Not reported	0
6	Replicate measurements	103
Total number of samples		1401

Appendix

A1. Methods

(A1.1) Seawater sampling

Seawater samples were collected from 10-liters Niskin bottles mounted on CTD-system and a stainless steel bucket for the surface. Samples for DIC/TA were transferred to Schott Duran[®] glass bottles (screw top) using sample drawing tubes. Bottles were filled smoothly from the bottom after overflowing double a volume while taking care of not entraining any bubbles, and lid temporarily with inner polyethylene cover and screw cap.

After all sampling finished, 2 mL of sample is removed from each bottle to make a headspace to allow thermal expansion, and then samples were poisoned with 0.2 mL of saturated HgCl₂ solution and covered tight again.

(A1.2) Measurement

The unit for DIC measurement in the coupled DIC/TA analyzer consists of a coulometer with a quartz coulometric titration cell, a CO₂ extraction unit and a reference gas injection unit. The CO₂ extraction unit, which is connected to a bottle of 20 % v/v phosphoric acid and a carrier N₂ gas supply, includes a sample pipette (approx. 12 mL) and a CO₂ extraction chamber, two thermoelectric cooling units and switching valves. The coulometric titration cell and the sample pipette are water-jacketed and are connected to a thermostated (25 °C) water bath. The automated procedures of DIC analysis in seawater were as follows (Ishii et al., 1998):

- (a) Approximately 2 mL of 20 % v/v phosphoric acid was injected to an “extraction chamber”, *i.e.*, a glass tube with a coarse glass frit placed near the bottom. Purified N₂ was then allowed to flow through the extraction chamber to purge CO₂ and other volatile acids dissolved in the phosphoric acid.
- (b) A portion of sample seawater was delivered from the sample bottle into the sample pipette of CO₂ extraction unit by pressurizing the headspace in the sample bottle. After temperature of the pipette was recorded, the sample seawater was transferred into the extraction chamber and mixed with phosphoric acid to convert all carbonate species to CO₂ (aq).
- (c) The acidified sample seawater was then stripped of CO₂ with a stream of purified N₂. After being dehumidified in a series of two thermoelectric cooling units, the evolved CO₂ in the N₂ stream was introduced into the carbon cathode solution in the coulometric titration cell and then CO₂ was electrically titrated.

A2. Working reference material recipe

The surface seawater in the western North Pacific was taken until at least a half year ago. Seawater was firstly filtered by membrane filter (0.45 µm-mesh) using magnetic pump and transfer into large tank. After first filtration finished, corrected seawater in the tank was processed in cycle filtration again for 3 hours and agitated in clean condition air for 6 hours. On the next day, agitated 5 minutes to remove small bubbles on the tank and transfer to Schott Duran[®] glass bottles as same method as samples (Appendix A1.1) except for overflowing a

half of volume, not double. Created of headspace and poisoned with HgCl₂ was as same as samples, finally, sealed by ground glass stoppers lubricated with Apiezon[®] grease (L).

References

- Dickson, A. G., C. L. Sabine, and J. R. Christian (Eds.) (2007), Guide to best practices for ocean CO₂ measurements. *PICES Special Publication 3*, 191 pp.
- DOE (1994), Handbook of methods for the analysis of the various parameters of the carbon dioxide system in sea water; version 2. *A. G. Dickson and C. Goyet (eds), ORNL/CDIAC-74*.
- Ishii, M., H. Y. Inoue, H. Matsueda, and E. Tanoue (1998), Close coupling between seasonal biological production and dynamics of dissolved inorganic carbon in the Indian Ocean sector and the western Pacific Ocean sector of the Antarctic Ocean, *Deep Sea Res. Part I*, **45**, 1187–1209, doi:10.1016/S0967-0637(98)00010-7.
- Johnson, K. M., A. E. King and J. McN. Sieburth (1985), Coulometric TCO₂ analyses for marine studies; an introduction. *Marine Chemistry*, **16**, 61–82.
- Johnson, K. M., J. M. Sieburth, P. J. L. Williams and L. Brändström (1987), Coulometric total carbon dioxide analysis for marine studies: Automation and calibration. *Marine Chemistry*, **21**, 117–133.
- Swift, J. H. (2010): Reference-quality water sample data, Notes on acquisition, record keeping, and evaluation. *IOCCP Report No.14, ICPO Pub. 134*, 2010 ver.1.

7. *Total Alkalinity (TA)*

30 September 2023

(14) Personnel

SAKAMOTO Naoaki

TANI Masanobu

TANIZAKI Chiho

(15) Station occupied

A total of 38 stations (Leg 1: 24, Leg 2: 14) were occupied for total alkalinity (TA). Station location and sampling layers of them are shown in Figures C.7.1 and C.7.2, respectively.




Figure C.7.1. Location of observation stations of TA. Closed and open circles indicate sampling and no-sampling stations, respectively.




Figure C.7.2. Distance-depth distribution of sampling layers of TA.

(16) Instrument

The measurement of TA was carried out with DIC/TA analyzers (Nihon ANS Co. Ltd., Japan). The methodology that these analyzers use is based on an open titration cell. We used two analyzers concurrently. These analyzers are designated as apparatus A and B.

(17) Sampling and measurement

The procedure of seawater sampling of TA bottles and poisoning with mercury (II) chloride (HgCl_2) were based on the Standard Operating Procedure (SOP) described in PICES Special Publication 3 (Dickson et al., 2007). Details are shown in Appendix A1 in C.6.

TA measurement is based on a one-step volumetric addition of hydrochloric acid (HCl) to a known amount of sample seawater with prompt spectrophotometric measurement of excess acid using the sulfonephthalein indicator bromo cresol green sodium salt (BCG) (Breland and Byrne, 1993). We used a mixed solution of HCl, BCG, and sodium chloride (NaCl) as reagent. Details of measurement are shown in Appendix A1.

(18) Calculation

(5.1) Volume of sample seawater

The volumes of pipette V_s using in apparatus A and B was calibrated gravimetrically in our laboratory. Table C.7.1 shows the summary.

Table C.7.1. Summary of sample volumes of seawater V_s for TA measurements.

Apparatus	V_s / mL
A	41.4764
B	43.0361

(5.2) pH_T calculation in spectrophotometric measurement

The data of absorbance A and pipette temperature T (in $^{\circ}\text{C}$) were processed to calculate pH_T (in total hydrogen ion scale; details shown in Appendix A1 in C.8) and the concentration of excess acid $[\text{H}^+]_T$ (mol kg^{-1}) in the following equations (C7.1)–(C7.3) (Yao and Byrne, 1998),

$$\begin{aligned} \text{pH}_T &= -\log_{10}([\text{H}^+]_T) \\ &= 4.2699 + 0.02578 \cdot (35 - S) + \log\{(R_{25} - 0.00131) / (2.3148 - 0.1299 \cdot R_{25})\} \\ &\quad - \log(1 - 0.001005 \cdot S) \quad (\text{C7.1}) \end{aligned}$$

$$R_{25} = R_T \cdot \{1 + 0.00909 \cdot (25 - T)\} \quad (\text{C7.2})$$

$$R_T = (A_{616}^{\text{SA}} - A_{616}^{\text{S}} - A_{730}^{\text{SA}} + A_{730}^{\text{S}}) / (A_{444}^{\text{SA}} - A_{444}^{\text{S}} - A_{730}^{\text{SA}} + A_{730}^{\text{S}}). \quad (\text{C7.3})$$

In the equation (C7.1), R_T is absorbance ratio at temperature T , R_{25} is absorbance ratio at temperature 25°C and S is salinity. $\overline{A}_{\lambda}^{\text{S}}$ and $\overline{A}_{\lambda}^{\text{SA}}$ denote absorbance of seawater before and after acidification, respectively, at wavelength λ nm.

(5.3) TA calculation

The calculated $[\text{H}^+]_T$ was then combined with the volume of sample seawater V_s , the volume of titrant V_A added to the sample, and molarity of hydrochloric acid HCl_A (in mmol L^{-1}) in the titrant to determine to TA concentration A_T (in $\mu\text{mol kg}^{-1}$) as follows:

$$A_T = (-[\text{H}^+]_T \cdot (V_s + V_A) \cdot \rho_{\text{SA}} + \text{HCl}_A \cdot V_A) / (V_s \cdot \rho_{\text{S}}) \quad (\text{C7.4})$$

ρ_{S} and ρ_{SA} denote the density of seawater sample before and after the addition of titrant, respectively. Here we assumed that ρ_{SA} is equal to ρ_{S} , since the density of titrant has been adjusted to that of seawater by adding NaCl and the volume of titrant (approx. 2.5 mL) is no more than approx. 6 % of seawater sample.

Finally, the value of A_T was multiplied by 1.00067 ($= 300.2 / 300.0$) to correct dilution effect in A_T induced by addition of HgCl_2 solution.

(19) Standardization of HCl reagent

HCl reagents were prepared in our laboratory (Appendix A2) and divided into bottles (HCl batches). HCl_A in the bottles were determined using measured CRMs provided by Dr. Andrew G. Dickson in Scripps Institution of Oceanography. Table C.7.2 provides information about the CRM batch used during this cruise.

Table C.7.2. Certified A_T and standard deviation of CRM. Unit of A_T is $\mu\text{mol kg}^{-1}$. More information is available at the NOAA web site (https://www.ncei.noaa.gov/access/ocean-carbon-acidification-data-system/oceans/Dickson_CRM/batches.html).

Batch number	160
A_T	2212.44 ± 0.67
Salinity	33.414

The CRM measurement was carried out at every station. The apparent HCl_A of the titrant was determined from CRM using equation (C7.4).

HCl_A was assigned for each HCl batches for each apparatus, as summarized in Table C.7.3 and detailed in Figure C.7.3.

Table C.7.3. Summary of assigned HCl_A for each HCl batches. The reported values are means and standard deviations. Unit is mmol L^{-1} .

Apparatus	HCl Batch	HCl_A
A	A_1	49.7591 ± 0.0237 (N=39)
	A_2	49.7525 ± 0.0279 (N=39)
	A_3	49.7954 ± 0.0182 (N=29)
	A_4	49.8012 ± 0.0117 (N=17)
B	B_1	49.8141 ± 0.0266 (N=33)
	B_2	49.8269 ± 0.0255 (N=42)
	B_3	49.8381 ± 0.0170 (N=30)
	B_4	49.8797 ± 0.0291 (N=11)




Figure C.7.3. Results of HCl_A measured by apparatus (a) A and (b) B. The HCl batch names are indicated at the top of each graph, and vertical lines denote the day when the HCl batch was switched. The red solid, dashed, and dotted lines denote the mean and the mean \pm twice the S.D. and thrice the S.D. for each HCl batches, respectively.

The precisions of HCl_A , defined as the coefficient of variation (= S.D. / mean), were 0.0235–0.0561 % for apparatus A and 0.0341–0.0583 % for apparatus B. They correspond to 0.52–1.24 $\mu\text{mol kg}^{-1}$ and 0.75–1.29 $\mu\text{mol kg}^{-1}$ in A_T of CRM batch 160, respectively.

(20) Quality Control

(7.1) Replicate and duplicate analyses

We took replicate (pair of water samples taken from a single Niskin bottle) and duplicate (pair of water samples taken from different Niskin bottles closed at the same depth) samples of A_T throughout the cruise. Table C.7.4 summarizes the results of the measurements with each apparatus. Figures C.7.4–C.7.5 show details of the results. The calculation of the standard deviation from the difference of sets of measurements was based on a procedure (SOP 23) in DOE (1994).

Table C.7.4. Summary of replicate and duplicate measurements. Unit is $\mu\text{mol kg}^{-1}$.

Measurement	Apparatus A	Apparatus B
	Average magnitude of difference \pm S.D.	
Replicate	0.8 ± 0.7 (N=56)	1.0 ± 0.9 (N=56)
Duplicate	0.8 ± 0.7 (N=6)	0.6 ± 0.5 (N=4)




Figure C.7.4. Results of (left) replicate and (right) duplicate measurements during the cruise versus (a) station number, (b) pressure, and (c) A_T determined by apparatus A. The green lines denote the averages of the measurements. The bottom panels (d) show histograms of the measurements.




Figure C.7.5. Same as Figure C.7.4, but for apparatus B.

(7.2) Measurements of CRM and working reference materials

The precision of the measurements was monitored by using the CRMs and working reference materials bottled in our laboratory (Appendix A2 in C.6). The measurements of the CRMs and working reference materials were the same those used to measure DIC (see (6.2) in C.6), except that the CRM measurement was repeated 3 times from the same bottle. Table C.7.5 summarizes the differences in the repeated measurements of the CRMs, the mean A_T of the CRM measurements, and the mean A_T of the working reference material measurements. Figures C.7.6–C.7.8 show detailed results.

Table C.7.5. Summary of difference and mean of A_T in the repeated measurements of CRM and the mean A_T of the working reference material. These data are based on good measurements. Unit is $\mu\text{mol kg}^{-1}$.

HCl Batches	CRM	Working reference material	
	Average magnitude of difference \pm S.D.	Mean Ave. \pm S.D.	Mean Ave. \pm S.D.
A_1	0.7 ± 0.5 (N=13)	2212.4 ± 1.0 (N=13)	2299.2 ± 1.0 (N=6)
A_2	0.8 ± 0.6 (N=13)	2212.4 ± 1.2 (N=13)	2299.2 ± 1.2 (N=7)
A_3	0.7 ± 0.5 (N=10)	2212.4 ± 0.7 (N=10)	2299.6 ± 1.2 (N=6)
A_4	0.4 ± 0.3 (N=6)	2212.4 ± 0.5 (N=6)	2299.9 ± 1.1 (N=3)
B_1	0.9 ± 0.7 (N=11)	2212.4 ± 1.1 (N=11)	2301.7 ± 1.0 (N=6)
B_2	1.3 ± 1.0 (N=14)	2212.4 ± 0.8 (N=14)	2301.2 ± 1.2 (N=6)
B_3	0.9 ± 0.7 (N=10)	2212.4 ± 0.4 (N=10)	2301.5 ± 2.4 (N=6)
B_4	0.9 ± 0.7 (N=4)	2212.6 ± 1.4 (N=4)	2300.5 ± 0.7 (N=2)




Figure C.7.6. The absolute difference (R) of A_T in repeated measurements of CRM determined by apparatus (a) A and (b) B. The solid line indicates the average of R (\bar{R}). The dashed and dotted lines denote the upper warning limit ($2.512\bar{R}$) and upper control limit ($3.267\bar{R}$), respectively (see Dickson et al., 2007).




Figure C.7.7. The mean A_T of measurements of CRM. The panels show the results for apparatus (a) A and (b) B. The solid line indicates the mean of the measurements. The dashed and dotted lines denote the upper/lower warning limit (mean \pm 2S.D.) and the upper/lower control limit (mean \pm 3S.D.), respectively. The gray dashed line denotes certified A_T of CRM. The labels at the top of the graph and vertical lines have the same meaning as in Figure C.7.3.




Figure C.7.8. Calculated A_T of working reference material measured by apparatus (a) A and (b) B. The solid, dashed and dotted lines have the same meaning as in Figure C.7.7. The labels at the top of the graph and vertical lines have the same meaning as in Figure C.7.3.

(7.3) Comparisons with other CRM batches

At every few stations, other CRM batches (155 and 157) were measured to provide comparisons with batch 160 to confirm the determination of A_T in our measurements. For these CRM measurements, A_T was calculated from HCl_A determined from batch 160 measurement. Figures C.7.9 show the differences between the calculated and certified A_T .




Figure C.7.9. The differences between the calculated A_T from batch 160 measurements and the certified A_T . The panels show the results for apparatus (a) A and (b) B. The labels at the top of the graph and vertical lines have the same meaning as in Figure C.7.3. Colors indicate CRM batches; red: 155 and green: 157.

(7.4) Quality control flag assignment

A quality control flag value was assigned to the TA measurements (Table C.7.6) using the code defined in the IOCCP Report No.14 (Swift, 2010).

Table C.7.6. Summary of assigned quality control flags.

Flag	Definition	Number of samples
2	Good	1281
3	Questionable	3
4	Bad (Faulty)	5
5	Not reported	0
6	Replicate measurements	112
Total number of samples		1401

Appendix

A1. Methods

(A1.1) Measurement

The unit for TA measurements in the coupled DIC/TA analyzer consists of sample treatment unit with a calibrated sample pipette and an open titration cell that are water-jacketed and connected to a thermostated water bath (25 °C), an auto syringe connected to reagent bottle of titrant stored at 25 °C, and a double-beam spectrophotometric system with two CCD image sensor spectrometers combined with a high power Xenon lamp. The mixture of 0.05 N HCl and 40 $\mu\text{mol L}^{-1}$ BCG in 0.65 M NaCl solution was used as reagent to automatically titrate the sample as follows:

- (a) A portion of sample seawater was delivered into the sample pipette (approx. 42 mL) following sample delivery into the DIC unit for a measurement. After the temperature in the pipette was recorded, the sample was transferred into a cylindrical quartz cell.
- (b) An absorption spectrum of sample seawater in the visible light domain was then measured, and the absorbances were recorded at wavelengths of 444 nm, 509 nm, 616 nm, and 730 nm as well as the temperature in the cell.
- (c) The titrant that contains HCl was added to the sample seawater by the auto syringe so that pH of sample seawater altered in the range between 3.85 and 4.05.
- (d) While the acidified sample was being stirred, the evolved CO₂ was purged with the stream of purified N₂ bubbled into the sample at approx. 200 mL min⁻¹ for 5 minutes.
- (e) After the bubbled sample steadied down for 1 minute, the absorbance of BCG in the sample was measured in the same way as described in (b), and pH (in total hydrogen ion scale, pH_T) of the acidified seawater was precisely determined spectrophotometrically.

A2. HCl reagents recipes

0.05 N HCl and 40 $\mu\text{mol L}^{-1}$ BCG in 0.65 M NaCl solution

Dissolve 0.30 g of BCG and 190 g of NaCl in roughly 1.5 L of deionized water (DW) in a 5 L flask, and slowly add 200 mL concentrated HCl. After the powders completely dissolved, dilute with DW to a final volume of 5 L.

References

- Breland II, J. A. and R. H. Byrne (1993), Spectrophotometric procedures for determination of sea water alkalinity using bromocresol green, *Deep-Sea Res. I*, 470, 629–641.
- Dickson, A. G., C. L. Sabine, and J. R. Christian (Eds.) (2007), Guide to best practices for ocean CO₂ measurements. PICES Special Publication 3, 191 pp.
- DOE (1994), Handbook of methods for the analysis of the various parameters of the carbon dioxide system in sea water; version 2. *A. G. Dickson and C. Goyet (eds), ORNL/CDIAC-74.*
- Yao, W. and R. H. Byrne (1998), Simplified seawater alkalinity analysis: Use of linear array spectrometers. *Deep-Sea Res. I*, 45, 1383–1392.
- Swift, J. H. (2010): Reference-quality water sample data, Notes on acquisition, record keeping, and evaluation. *IOCCP Report No.14, ICPO Pub. 134, 2010 ver.1.*

8. *pH*

30 September 2023

(21) Personnel

SAKAMOTO Naoaki

TANI Masanobu

TANIZAKI Chiho

(22) Station occupied

A total of 38 stations (Leg 1: 24, Leg 2: 14) were occupied for pH. Station location and sampling layers of them are shown in Figures C.8.1 and C.8.2, respectively.




Figure C.8.1. Location of observation stations of pH. Closed and open circles indicate sampling and no-sampling stations, respectively.




Figure C.8.2. Distance-depth distribution of sampling layers of pH.

(23) Instrument

The measurement of pH was carried out with a pH analyzer (Nihon ANS Co. Ltd, Japan).

(24) Sampling and measurement

Methods of seawater sampling, poisoning, spectrophotometric measurements using the indicator dye *m*-cresol purple (hereafter *m*CP) and calculation of pH_T (on the total hydrogen ion scale; Appendix A1) were based on Saito et al. (2008). The pH_T is calculated from absorbance ratio (R) with the following equations,

$$\text{pH}_T = \text{p}K_2 + \log_{10}\{(R - 0.0069)/(2.222 - 0.1331 \cdot R)\} \quad (\text{C8.1})$$

$$R = (A_{578}^{\text{SD}} - A_{578}^{\text{S}} - A_{730}^{\text{SD}} + A_{730}^{\text{S}})/(A_{434}^{\text{SD}} - A_{434}^{\text{S}} - A_{730}^{\text{SD}} + A_{730}^{\text{S}}) \quad (\text{C8.2})$$

where $\text{p}K_2$ is the acid dissociation constant of *m*CP,

$$\text{p}K_2 = 1245.69/T + 3.8322 + 0.00211 \cdot (35 - S) \quad (\text{C8.3})$$

(293 K $\leq T \leq$ 303 K, 30 $\leq S \leq$ 37).

A_{λ}^{S} and A_{λ}^{SD} in equation (C8.2) are absorbance of seawater itself and dye plus seawater, respectively, at wavelength λ (nm). The value of $\text{p}K_2$ in equation (C8.3) is expressed as a function of temperature T (in Kelvin) and salinity S (in psu). Finally, pH_T is reported as the value at temperature of 25 °C. Details are shown in Appendix A1.

(25) pH perturbation caused by addition of *m*-cresol purple solution

The *m*CP solution using as indicator dye was prepared in our laboratory (Appendix A2) and was subdivided into some bottles (*m*CP batches) that attached to the apparatus. The injection of *m*CP solution perturbs the sample pH_T slightly because the acid-base equilibrium of the seawater is disrupted by the addition of the dye acid-base pair (Dickson et al., 2007).

Before applying R to the equation (C8.1), the measured R in the sample was corrected to that value expected to be unperturbed by the addition of the dye (Dickson et al., 2007; Clayton and Byrne, 1993). The magnitude of the perturbation (ΔR) was calculated empirically from that by the second addition of the dye and absorbance ratio measurement as follows:

$$\Delta R = R_2 - R_1, \quad (\text{C8.4})$$

where R_1 and R_2 are the absorbance ratio after the initial addition of dye solution in the sample measurement and after the second addition in the experimental measurement, respectively. Because the value of ΔR depends on the pH_T of sample, we expressed ΔR as a quadratic function of R_1 based on experimental ΔR measurement obtained at this cruise as follows:

$$\Delta R = C_2 \times R_1^2 + C_1 \times R_1 + C_0. \quad (\text{C8.5})$$

In each measurement for a station, ΔR was measured for about 10 samples from various depths to obtain wide range of R_1 and experimental ΔR data. For each *m*CP batch bottle, coefficients (C_0 , C_1 and C_2) were calculated by equation (C8.5), and ΔR was evaluated for each R_1 . The coefficients for each *m*CP batch are showed in Table C.8.1. The plots and function curves are illustrated in Figure C.8.3.

Table C.8.1. Summary of coefficients; C_2 , C_1 and C_0 in $\Delta R = C_2 \times R_1^2 + C_1 \times R_1 + C_0$.

Stations	<i>m</i> CP batch	C_2	C_1	C_0
2–26	1	–7.12302E–03	1.84608E–04	7.27697E–03
27–46	2	1.40192E–04	–1.67665E–02	1.35675E–02




Figure C.8.3. The function curve of the $\Delta R (= R_2 - R_1)$ vs R_1 for (left) first and (right) second *mCP* batch of solution shown in Table C.8.1.

(26) Quality Control

(6.1) Replicate and duplicate analyses

We took replicate (pair of water samples taken from a single Niskin bottle) and duplicate (pair of water samples taken from different Niskin bottles closed at the same depth) samples for pH_T determination throughout the cruise. Table C.8.2 summarizes the results of the measurements. Figure C.8.4 shows details of the results. The calculation of the standard deviation from the difference of sets of measurements was based on a procedure (SOP 23) in DOE (1994).

Table C.8.2. Summary of replicate and duplicate measurements of pH_T .

Measurement	Average magnitude of difference \pm S.D.
Replicate	0.0020 \pm 0.0019 (N=110)
Duplicate	0.0026 \pm 0.0021 (N=10)




Figure C.8.4. Results of (left) replicate and (right) duplicate measurements during the cruise versus (a) station number, (b) pressure and (c) pH_T . The green lines denote the averages of the measurements. The bottom panels (d) show histograms of the measurements.

(6.2) Measurements of CRM and working reference materials

The precision of the measurements was monitored by using the CRMs and working reference materials bottled in our laboratory (Appendix A2 in C.6). Although the pH_T value of the CRM was not assigned, it could be calculated from certified parameters of DIC and TA (https://www.ncei.noaa.gov/access/ocean-carbon-acidification-data-system/oceans/Dickson_CRM/batches.html) based on the chemical equilibrium of the carbonate system (Lueker et al., 2000). The pH_T of the CRM (batch 157) was calculated to be 7.8405. Working reference material measurements were carried out first at every station. If the results of the measurements were confirmed to be good, measurements on seawater samples were begun. CRM (batch 157) measurements were done at every few (about 3) stations. The measurement for seawater sample and working reference material was made once for a single bottle, and that for CRM was made twice. Table C.8.3 summarizes the means of difference of pH_T between two measurements and pH_T values for a CRM bottle and the means of the pH_T value for a working reference material for each *mCP* batch. Figures C.8.5–C.8.7 show detailed results.

Table C.8.3. Summary of difference and means of the pH_T values for two measurements for a CRM bottle, and mean of pH_T for a working reference material, which was calculated with data with good measurements.

CRM	Working reference
-----	-------------------

<i>mCP</i> Batches	material		
	Magnitude of difference	Mean	Mean
	Ave. \pm S.D.	Ave. \pm S.D.	Ave. \pm S.D.
1	0.0012 \pm 0.0011 (N=12)	7.8373 \pm 0.0017 (N=12)	7.8985 \pm 0.0014 (N=25)
2	0.0010 \pm 0.0008 (N=7)	7.8418 \pm 0.0011 (N=7)	7.9033 \pm 0.0023 (N=18)




Figure C.8.5. The absolute difference (R) of pH_T between two measurements of a CRM bottle. The mCP batch names are shown above the graph, and vertical lines denote the day mCP batches were changed. The solid, dashed and dotted lines denote the average range (\bar{R}), upper warning limit ($2.512\bar{R}$) and upper control limit ($3.267\bar{R}$) for each mCP batch bottle, respectively (see Dickson et al., 2007).




Figure C.8.6. The mean of pH_T values between two measurements of a CRM bottle. The mCP batch names are shown above the graph, and vertical lines denote the day when the mCP batch was changed. The solid, dashed, and dotted lines denote the mean of measurements, upper/lower warning limit (mean \pm 2S.D.), and upper/lower control limit (mean \pm 3S.D.) for each mCP batch bottle, respectively (see Dickson et al., 2007). The gray dashed line denotes pH_T of CRM calculated from certified parameters.




Figure C.8.7. Same as C.8.6, but for working reference material.

(6.3) Quality control flag assignment

A quality control flag value was assigned to the pH measurements (Table C.8.4) using the code defined in the IOCCP Report No.14 (Swift, 2010).

Table C.8.4. Summary of assigned quality control flags.

Flag	Definition	Number of samples
2	Good	1280
3	Questionable	4
4	Bad (Faulty)	5
5	Not reported	2
6	Replicate measurements	110
Total number of samples		1401

(6.4) Comparison at cross-stations during the cruise

There was a cross-station during the cruise located at 42°N/165°E. At stations of Stn.26 and Stn.27, hydrocast sampling for pH_T was conducted two times at interval of 13 days. These profiles are shown in Figure C.8.8.




Figure C.8.8. Comparison of pH_T observed at same location in different legs of this cruise: 42°N/165°E (stations 26 and 27). The red and green circles denote station 26 and station 27, respectively. Triangles denote the difference in pH_T measured at same depth in different legs.

(6.5) Comparison at cross-stations of WHP cruises

We compared pH_T data of this cruise and other WHP cruises by JMA, Japan Agency for Marine-Earth Science and Technology (JAMSTEC) and Scripps Institution of Oceanography (SIO) at cross points. Summary of the comparisons are shown in Figure C.8.9(a) for cross point with WHP-P2 line (around 30°N/165°E), Figure C.8.9(b) for cross point with WHP-40N line (around 40°N/165°E), and Figure C.8.9(c) for cross point with WHP-P1 line (around

47°N/160°E). Data of other cruises are downloaded from the CCHDO web site (<https://cchdo.ucsd.edu>).




Figure C.8.9. Comparison of pH_T profiles at (a) 30°N/165°E (cross point with WHP-P2 line), (b) 40°N/165°E (cross point with WHP-40N line), and (c) 47°N/160°E (cross point with WHP-P1 line). Circles and triangles denote good and questionable values, respectively. The red ones show this cruise.

Appendix

A1. Methods

(A1.1) Seawater sampling

Seawater samples were collected from 10-liters Niskin bottles mounted on CTD-system and a stainless steel bucket for the surface. Samples for pH were transferred to Schott Duran® glass bottles using sample drawing tubes. Bottles were filled smoothly from the bottom after overflowing double a volume while taking care of not entraining any bubbles, and lid temporarily with ground glass stoppers.

After all sampling finished, 2 mL of sample is removed from each bottle to make a headspace to allow thermal expansion. Although the procedure is differed from Standard Operating Procedure (SOP) described in PICES Special Publication 3, SOP-2 (Dickson, 2007), poisoned with 0.2 mL of saturated HgCl₂ solution to prevent change in pH_T caused by biological activity. Finally, samples were sealed with ground glass stoppers lubricated with Apiezon® grease (L).

(A1.2) Measurement

Custom-made pH analyzer (2009 model; Nihon ANS) was prepared and operated in the cruise. The analyzer comprised of a sample dispensing unit, a pre-treatment unit combined with an automated syringe, and two (sample and reference) spectrophotometers combined with a high power xenon light source. Spectrophotometric cell was made of quartz tube that has figure of “U”. This cell was covered with stainless bellows tube to keep the external surface dry and for total light to reflect in the tube. The temperature of the cell was regulated to 25.0 ± 0.1 °C by means of immersing the cell into the thermostat bath, where the both ends of bellows tube located above the water surface of the bath. Spectrophotometer, cell and light source were connected with optical fiber.

The analysis procedure was as follows:

- a) Seawater was ejected from a sample loop.
- b) A portion of sample was introduced into a sample loop including spectrophotometric cell. The spectrophotometric cell was flushed two times with sample in order to remove air bubbles.
- c) An absorption spectrum of seawater in the visible light range was measured. Absorbance at wavelengths of 434 nm, 488 nm, 578 nm and 730 nm as well as cell temperature were recorded. To eject air bubbles from the cell, the sample was moved four times and the absorbance was recorded at each stop.
- d) 10 µl of indicator *m*CP was injected to the loop.
- e) Circulating 2 minutes 40 seconds through the loop tube, seawater sample and indicator dye was mixed together.
- f) Absorbance of *m*CP plus seawater was measured in the same way described above (c).

(A1.3) Calculation

In order to state clearly the scale of pH, we mention “pH_T” that is defined by equation (C8.A1.3.1),

$$\overline{\text{pH}_T = -\log_{10}([\text{H}^+]_T/C^0)} \quad (\text{C8.A1.3.1})$$

where $[\text{H}^+]_T$ denotes the concentration of hydrogen ion expressed in the total hydrogen ion

scale. $[\text{H}^+]_T = [\text{H}^+]_F(1 + [\text{SO}_4]_T/K_{\text{HSO}_4^-})$, where $[\text{H}^+]_F$ is the concentration of free

hydrogen ion, $[\text{SO}_4]_T$ is the total concentration of sulphate ion and $\overline{K_{\text{HSO}_4^-}}$ is acid dissociation constant of hydrogen sulphate ion (Dickson, 1990). C^0 is the standard value of concentration (1 mole per kilogram of seawater, mol kg⁻¹). The pH_T was reported as the value at temperature of 25 °C in “total hydrogen ion scale”.

pH_T was calculated from the measured absorbance (A) based on the following equations (C8.A1.3.2) and (C8.A1.3.3), which are the same as (C8.1) and (C8.2), respectively.

$$\overline{\text{pH}_T = \text{p}K_2 + \log_{10}([\text{I}^{2-}]/[\text{HI}^-])} \\ \overline{= \text{p}K_2 + \log_{10}\{(R - 0.0069)/(2.222 - 0.1331 \cdot R)\}} \quad (\text{C8.A1.3.2})$$

$$\overline{R = (A_{578}^{\text{SD}} - A_{578}^{\text{S}} - A_{730}^{\text{SD}} + A_{730}^{\text{S}})/(A_{434}^{\text{SD}} - A_{434}^{\text{S}} - A_{730}^{\text{SD}} + A_{730}^{\text{S}})} \quad (\text{C8.A1.3.3})$$

where $\text{p}K_2$ is the acid dissociation constant of *m*CP. $[\text{I}^{2-}] / [\text{HI}^-]$ is the ratio of *m*CP base form (I^{2-}) concentration over acid form (HI^-) concentration which is calculated from the corrected absorbance ratio (R) shown in the section 8(5) and the ratios of extinction coefficients (Clayton and Byrne, 1993). $\overline{A_{\lambda}^{\text{S}}}$ and $\overline{A_{\lambda}^{\text{SD}}}$ in equation (C8.A1.3.3) are absorbance of seawater itself and dye plus seawater, respectively, at wavelength λ (nm). The value of $\text{p}K_2$ ($\overline{= -\log_{10}(K_2/k^0)}$, $k^0 = 1 \text{ mol kg}^{-1}$) had also been expressed as a function of temperature T (in Kelvin) and salinity S (in psu) by Clayton and Byrne (1993), but the calculated value has been subsequently corrected by 0.0047 on the basis of a reported pH_T value accounting for “tris” buffer (DelValls and Dickson, 1998):

$$\overline{\text{p}K_2 = \text{p}K_2(\text{Clayton \& Byrne, 1993}) + 0.0047} \\ \overline{= 1245.69/T + 3.8322 + 0.00211 \cdot (35 - S).} \quad (\text{C8.A1.3.4}) \\ (293 \text{ K} \leq T \leq 303 \text{ K}, 30 \leq S \leq 37)$$

Finally, pH_T determined at a temperature t (pH_T(t), with t in °C) was corrected to the pH_T at 25.00 °C (pH_T(25)) with the following equation (Saito et al., 2008).

$$\overline{(\text{pH}_T(t) - \text{pH}_T(25))/(t - 25.00)}$$

$$= (2.00170 - 0.735594 \cdot \text{pH}_T(25) + 0.0896112 \cdot \text{pH}_T(25)^2 - 0.00364656 \cdot \text{pH}_T(25)^3)$$

(C8.A1.3.5)

A2. pH indicator

Indicator *m*-cresol purple (*m*CP) solution

Add 0.67 g *m*CP to 500 mL deionized water (DW) in a borosilicate glass flask. Pour DW slowly into flask to weight of 1 kg (*m*CP + DW), and mix well to dissolve *m*CP. Regulate the pH (free hydrogen ion scale) of indicator solution to 7.9 ± 0.1 by small amount of diluted NaOH solution (approx. 0.25 mol L^{-1}) if the pH was out of the range. The pH of indicator solution was monitored using glass electrode pH meter. The reagent had not been refining.

References

- Clayton T.D. and R.H. Byrne 1993. Spectrophotometric seawater pH measurements: total hydrogen ion concentration scale calibration of *m*-cresol purple and at-sea results. *Deep-Sea Res. I*, **40**, 2115–2129.
- DelValls, T. A. and A. G. Dickson, 1998. The pH of buffers based on 2-amino-2-hydroxymethyl-1,3-propanediol ('tris') in synthetic sea water. *Deep-Sea Res. I*, **45**, 1541-1554.
- Dickson, A.G. 1990. Standard potential of the reaction: $\text{AgCl(s)} + 1/2 \text{H}_2(\text{g}) = \text{Ag(s)} + \text{HCl(aq)}$, and the standard acidity constant of the ion HSO_4^- in synthetic sea water from 273.15 to 318.15 K. *J. Chem. Thermodynamics*, **22**, 113–127.
- Dickson, A.G., Sabine, C.L. and Christian, J.R. (Eds.) 2007. Guide to best practices for ocean CO_2 measurements. *PICES Special Publication* 3, 191 pp.
- Lueker, T.J, A.G. Dickson and C.D. Keeling, 2000. Ocean $p\text{CO}_2$ calculated from dissolved inorganic carbon, alkalinity, and equations for K_1 and K_2 : validation based on laboratory measurements of CO_2 in gas and seawater at equilibrium. *Marine Chem.*, **70**, 105-119.
- Saito, S., M. Ishii, T. Midorikawa and H.Y. Inoue 2008. Precise Spectrophotometric Measurement of Seawater pH_T with an Automated Apparatus using a Flow Cell in a Closed Circuit. *Technical Reports of Meteorological Research Institute*, **57**, 1–28.
- Swift, J. H. (2010): Reference-quality water sample data, Notes on acquisition, record keeping, and evaluation. *IOCCP Report No.14, ICPO Pub. 134, 2010 ver.1*